Safety Data Sheet (SDS)
RockShox Fork Oil Medium 5wt

Revision Date: 9/1/2023

Section 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Identity	RockShox Fork Oil Medium 5wt
Alternate Names	RockShox Fork Oil Medium 5wt
Unique Formula Identifier	YQGX-K2E0-V00M-9YU6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended Uses and Uses Advised Against	See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet

Company Name	Torco International Corporation 1720 S CARLOS AVE ONTARIO, CA 91761
Customer service:	(909) 980-1495
1.4. Emergency telephone number	(800) 424-9300
Emergency	
24 hour Emergency Telephone No.	(909) 980-1495

Section 2. Hazard identification of the product

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aspiration hazard, category 1;H304 — May be fatal if swallowed and enters airways.

No applicable CLP categories.

2.2. Label elements

According to REGULATION (EU) 2020/878 amending Regulations EU 2015/830 and (EC) No 1907/2006

No applicable CLP categories.



Danger

H304 May be fatal if swallowed and enters airways.

P501 Dispose of contents or container in accordance with local and national regulations.
P405 Store locked up.

2.3. Other hazards

This product contains no PBT/vPvB chemicals.
This product contains no endocrine disrupting chemicals.

Section 3. Composition/information on ingredients

3.2. Mixtures

If the product contains substances that present a hazard according to Regulation (EC) No. 1272/2008 [CLP/GHS], they are listed below.

Ingredient/Chemical Designations	Weight %	EC No. 1272/2008 Classification*	Notes
Distillates (petroleum), hydrotreated light naphthenic **CAS Number: 0064742-53-6** **EC No. 265-156-6** **Index No.: 649-466-00-2**	**25 - 50**	**Aspiration hazard, category 1;H304**	**H; L** ^CLP 3.1
Distillate (petroleum) hydrotreated heavy naphthenic **CAS Number: 0064742-52-5** **EC No. 265-155-0** **Index No.: 649-465-00-7**	**25 - 50**	**Aspiration hazard, category 1;H304**	**H; L** ^CLP 3.1

^CLP 31 Reference EC No. 1272/2008 1.1.3.1. Notes relating to the identification, classification and labelling of substances (Table 3.1).

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eye Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion DO NOT INDUCE VOMITING! If swallowed, vomiting may occur spontaneously. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth thoroughly. Get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Overview If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhea. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Inhalation May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically. IF SWALLOWED: Do NOT induce vomiting.

Section 5. Fire-fighting measures

5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO_2, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

5.3. Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

Section 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Dispose of contents or container in accordance with local and national regulations.

6.3. Methods and material for containment and cleaning up

Slippery when spilled. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Local authorities should be advised if significant spillages cannot be contained.

6.4 Reference to other sections

See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

Section 7. Handling and storage

7.1. Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Avoid prolonged or repeated contact with skin. Avoid inhaling vapor and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Keep container tightly closed and in a cool, well-ventilated place.

Use properly labeled and closeable containers.
This material has the potential to be a static accumulator. Proper grounding and bonding procedures should be used during all bulk transfer operations.
Use product with caution around heat, sparks, pilot lights, static electricity and open flame.

7.2. Conditions for safe storage, including any incompatibilities

Storage Temperature: -50 - 50C (-58 - 122F)

For containers or container linings, use mild steel or high density polyethylene.
Do not use PVC.

Incompatible materials: Strong oxidizing agents and acids.

Store locked up.

7.3. Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0064742-52-5	Distillate (petroleum) hydrotreated heavy naphthenic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		National	No Established Limit
0064742-53-6	Distillates (petroleum), hydrotreated light naphthenic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		National	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m^3 OSHA PEL and 10 mg/m^3 ACGIH.

8.2. Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Skin protection is not required under normal conditions of use. Oil impervious gloves and oil impermeable apron recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Color: RED OILY LIQUID Physical State: Liquid

Odor Petroleum Odor

Odor threshold Not determined

pH No available information

Melting point / freezing point	No available information
Initial boiling point and boiling range	No available information
Flash Point	120°C
Evaporation rate (Ether = 1)	No available information
Flammability (solid, gas)	No available information
Upper/lower flammability or explosive limits	**Lower Explosive Limit:** No available information **Upper Explosive Limit:** No available information
Vapor pressure (Pa)	No available information
Vapor Density	No available information
Relative Density	0.884
Solubility in Water	Negligible
Partition coefficient n-octanol/water (Log Kow)	Not determined
Auto-ignition temperature	No available information
Decomposition temperature	No available information
Viscosity (cSt)	No available information
VOC Content	nil

9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

No available information

10.4. Conditions to avoid

Excessive heat and open flame.

10.5. Incompatible materials

Strong oxidizing agents and acids.

10.6. Hazardous decomposition products

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Section 11. Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	> 5,000.00, Rat - Category: NA	No data available	No data available	5.70, Rat - Category: NA	No data available
Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0064742-52-5	Distillate (petroleum) hydrotreated heavy naphthenic	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0064742-53-6	Distillates (petroleum), hydrotreated light naphthenic	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	---
Acute toxicity (dermal)	---	---
Acute toxicity (inhalation)	---	---
Skin corrosion/irritation	---	---
Serious eye damage/irritation	---	---
Respiratory sensitization	---	---
Skin sensitization	---	---
Germ cell mutagenicity	---	---
Carcinogenicity	---	---
Reproductive toxicity	---	---
STOT-single exposure	---	---
STOT-repeated exposure	---	---
Aspiration hazard	1	May be fatal if swallowed and enters airways.

11.2 Information on other hazards

11.2.1. Endocrine disrupting properties

This product contains no endocrine disrupting chemicals.

Section 12. Ecological information

12.1. Toxicity

Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be harmful: LL/EL/IL50 10-100 mg/L (to aquatic organisms) LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L	3hr IC50 Bacteria mg/L	Biodegradability %
Distillate (petroleum) hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus	---	---

Distillates (petroleum), hydrotreated light naphthenic - (64742-53-6)	---	---	---	---	---

12.2. Persistence and degradability

Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment.

12.3. Bioaccumulative potential

Contains components with the potential to bioaccumulate.

12.4. Mobility in soil

Liquid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile. Floats on water.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6 Endocrine disrupting properties

This product contains no endocrine disrupting chemicals.

12.7. Other adverse effects

No available information

Section 13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

Section 14. Transport information

	ADR/RID	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
14.3. Transport hazard class(es)	**DOT Hazard Class:** Not Applicable **Sub Class:** Not Applicable	**IMDG:** Not Applicable **Sub Class:** Not Applicable	**Air class:** Not Applicable **Sub Class:** Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable

14.5. Environmental hazards

Marine Pollutant: No;

14.6. Special precautions for user

No available information

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Section 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Legislation

REGULATION (EU) 2020/878 amending Regulations EU 2015/830 and (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH).
REGULATION (EC) 1272/2008 on the classification, labeling and packaging of substances and mixtures (CLP).

National Legislation

None noted.

15.2. Chemical Safety Assessment

No Chemical Safety Assessment has been carried out.

Section 16. Other information

Revision Date 9/1/2023

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

This information has been compiled from sources considered to be dependable and is accurate to the best of Torco International Corporation knowledge. Torco International Corporation makes no warranty whatsoever, expressed or implied, of MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, regarding the accuracy of such data or the results to be obtained from the use thereof. Torco International Corporation assumes no responsibility for injury to recipient or third persons, or for any damage to any property and recipient assumes all such risks.

End of Document