Life Needs Superior Bikes

2027



amsler
est. 1865
bikes & parts

superior.

superior.



Life Needs Superior Bikes

For every ride. For every rider.

Leben ist Bewegung. Jeder Tag bringt neue Wege, neue Herausforderungen und neue Gründe, nach draussen zu gehen. Superior baut Bikes für alle, die weiter, schneller, komfortabler oder einfach öfter fahren möchten. Unser neuer Claim «Life Needs Superior Bikes» bringt eine einfache Idee auf den Punkt: Ein Bike ist nicht nur ein Sportgerät. Es ist Teil eines aktiven Lebensstils, steht für Freiheit im Alltag und die Freude an Bewegung. Deshalb entwickeln wir ein umfassendes Bike-Sortiment für jeden Einsatzbereich – von Performance-Modellen und E-Bikes bis hin zu urbaner Mobilität und Kinderbikes.

La vie, c'est le mouvement. Chaque jour apporte de nouvelles routes, de nouveaux défis et de nouvelles raisons de sortir. Superior conçoit des vélos pour aller plus loin, plus vite et plus confortablement. «Life Needs Superior Bikes» exprime une idée simple: le vélo est bien plus qu'un sport. Il incarne un mode de vie actif, la liberté au quotidien et le plaisir de bouger. C'est pourquoi Superior propose une gamme complète, des modèles performance aux vélos électriques, urbains et pour enfants.

Inhaltsverzeichnis
Table des matières

ROAD
PHOTON 03 - 05
RR 06 - 07
XR GF Alu 08

GRAVEL
XR Gravel 10 - 16
XR GRA 32“ 18 - 19
iXR E-Gravel 21

E-MTB Full-Suspension
eXF 23 - 24

E-MTB Hardtail
eXP 26 - 29
eXP SUV (eBlox) 27 - 28

E-TOUR Urban
eBLOX (Man & Lady) 31 - 34

CITY e-Bikes
eFARAD (Lady) 36 - 39

MTB Full-Suspension
XF TEAM 41
XF RC Race 42 - 43
XF DC Trail 44 - 45

MTB Hardtail
XP 47 - 51
XC 52 - 58

JUNIOR
Junior 27.5“ 60 - 66
Junior 24“ & 20“ 67 - 82

TREKKING & CITY
BLOX 84 - 88

superior.





road

RR / XR GF

Superior Rennräder sind für puren Speed gebaut.
Aero optimiert und extrem leichte Rahmen bringen deine Performance direkt auf die Strasse. Ob Rennen, Training oder die Jagd nach Bestzeiten, eines ist sicher; Du bist schneller als erwartet.

Les vélos de route Superior sont conçus pour la vitesse. Aérodynamiques et ultralégers, ils offrent des performances maximales sur la route. En course, à l'entraînement ou contre le chrono: plus vite que prévu.

PHOTON 9.9

Matte Raw Carbon

CHF 7'699.–



FRAME SIZE	EAN	Quantity
XS		
S		
M		
L		
XL		
XXL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 6 Suitable Road Riding
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-50-01, Carbon RR Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, UDH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible.
FORK	RR Mid Modulus Carbon Fork
BOTTOM BRACKET	SHIMANO BB-72-41B, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-347S, ICR, OD53.5, IS49.5/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	ZY-THA19A, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	ZY-THA19A, TA12x165, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO DURA-ACE
SHIFTERS RIGHT	SHIMANO DURA-ACE
FRONT DERAILLEUR	SHIMANO DURA-ACE
REAR DERAILLEUR	SHIMANO DURA-ACE
CRANKSET	SHIMANO DURA-ACE
CASSETTE	SHIMANO DURA-ACE
CHAIN	SHIMANO XT CN-M8100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO DURA-ACE
ROTOR FRONT	SHIMANO RT-CL900, 160mm
BRAKE REAR	SHIMANO DURA-ACE
ROTOR REAR	SHIMANO RT-CL900, 140mm

WHEELS

WHEELSET FRONT	DT Swiss ARC 1100 DICUT® CSX, Carbon, CL, 12x100mm, Height 55mm, Tubeless Ready
WHEELSET REAR	DT Swiss ARC 1100 DICUT® CSX, Carbon, CL, 12x142mm, SH13, Height 55mm, Tubeless Ready
TIRE FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race
TIRE REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race

COCKPIT

HANDLEBAR	ONE Carbon Road Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizi:k Vento Antares R1, Carbon
SEATPOST	ONE Aero Carbon, 9mm offset
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	XS	S	M	L	XL	XXL
BB DROP (MM)	75	75	72,5	72,5	70	70
SEAT TUBE LENGTH (MM)	420	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	510	532	545	569	591	600
STACK HEIGHT (MM)	490	516	537	558	577	600
REACH (MM)	370	358	390	395	405	420
SEAT TUBE ANGLE	75°	74°	73,5°	73°	73°	72,5°
HEAD TUBE ANGLE	70,5°	71°	71,5°	72°	72°	73,5°
REAR CENTER (MM)	406	406	406	406	406	406
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
HANDLEBAR (MM)	380/70	380/90	380/110	400/110	400/130	400/13
CRANKSET (MM)	160, 52-37T	165, 52-37T	167.5, 52-37T	167.5, 52-37T	170, 52-37T	170, 52-
SEATPOST (MM)	320	320	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

PHOTON 9.8

Gloss Red Carbon

CHF 4'799.–



FRAME SIZE	EAN	Quantity
XS		
S		
M		
L		
XL		
XXL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 6 Suitable Road Riding
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-50-01, Carbon RR Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, UDH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible.
FORK	RR Mid Modulus Carbon Fork
BOTTOM BRACKET	SRAM DUB ROAD, PressFit, shell 41x86,5 mm
HEADSET	ACROS AIX-347S, ICR, OD53.5, IS49.5/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	ZY-THA19A, TA12x119, M12xP1.5x8.5L, Black
REARAXLE	ZY-THA19A, TA12x165, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS LEFT	SRAM FORCE AXS, electronic shifter
SHIFTERS RIGHT	SRAM FORCE AXS, electronic shifter
FRONT DERAILLEUR	SRAM FORCE E1 AXS, 2 speed
REAR DERAILLEUR	SRAM FORCE E1 AXS, 12 speed
CRANKSET	SRAM FORCE E1, DUB
CASSETTE	SRAM FORCE XG-1270, 12-speed, 10-36T
CHAIN	SRAM RIVAL, Flattop 12s/13s

BRAKING SYSTEM

BRAKE FRONT	SRAM FORCE AXS, hydraulic disc brake
ROTOR FRONT	SRAM Paceline, 160mm
BRAKE REAR	SRAM FORCE AXS, hydraulic disc brake
ROTOR REAR	SRAM Paceline, 140mm

WHEELS

WHEELSET FRONT	DT Swiss ARC ELEMENT DICUT®, Carbon, CL, 12x100mm, Height 50mm, Tubeless Ready
WHEELSET REAR	DT Swiss ARC ELEMENT DICUT®, Carbon, CL, 12x142mm, AXDR , Height 50mm, Tubeless Ready
TIRE FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race
TIRE REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race

COCKPIT

HANDLEBAR	ONE Carbon Road Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizi:k ARGO R5, Alloy
SEATPOST	ONE Aero Carbon, 9mm offset
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	XS	S	M	L	XL	XXL
BB DROP (MM)	75	75	72,5	72,5	70	70
SEAT TUBE LENGTH (MM)	420	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	510	532	545	569	591	600
STACK HEIGHT (MM)	490	516	537	558	577	600
REACH (MM)	370	358	390	395	405	420
SEAT TUBE ANGLE	75°	74°	73,5°	73°	73°	72,5°
HEAD TUBE ANGLE	70,5°	71°	71,5°	72°	72°	73,5°
REAR CENTER (MM)	406	406	406	406	406	406
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
HANDLEBAR (MM)	380/70	380/90	380/110	400/110	400/130	400/130
CRANKSET (MM)	160, 50-37T	165, 50-37T	165, 50-37T	170, 50-37T	170, 50-37T	170, 50-37T
SEAT POST (MM)	320	320	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

PHOTON 9.7

Matte Raw Carbon

CHF 3'699.–



FRAME SIZE	EAN	Quantity
XS		
S		
M		
L		
XL		
XXL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 6 Suitable Road Riding
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-50-01, Carbon RR Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, UDH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible.
FORK	RR Mid Modulus Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-347, ICR, OD53.5, IS49.5/28.6 - 40IPS
FRONT AXLE	ZY-THA19A, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	ZY-THA19A, TA12x165, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7150, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II
CASSETTE	SHIMANO 105 CS-R7101, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO 105 R7170, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL700, 160mm
BRAKE REAR	SHIMANO 105 R7170, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL700, 140mm

WHEELS

WHEELSET FRONT	DT Swiss ARC ELEMENT DICUT®, Carbon, CL, 12x100mm, Height 50mm, Tubeless Ready
WHEELSET REAR	DT Swiss ARC ELEMENT DICUT®, Carbon, CL, 12x142mm, SH11, Height 50mm, Tubeless Ready
TIRE FRONT	Schwalbe Lugano II, K-Guard, 32-622
TIRE REAR	Schwalbe Lugano II, K-Guard, 32-622

COCKPIT

HANDLEBAR	ONE Carbon Road Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Aero Carbon, 9mm offset
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	XS	S	M	L	XL	XXL
BB DROP (MM)	75	75	72,5	72,5	70	70
SEAT TUBE LENGTH (MM)	420	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	510	532	545	569	591	600
STACK HEIGHT (MM)	490	516	537	558	577	600
REACH (MM)	370	358	390	395	405	420
SEAT TUBE ANGLE	75°	74°	73,5°	73°	73°	72,5°
HEAD TUBE ANGLE	70,5°	71°	71,5°	72°	72°	73,5°
REAR CENTER (MM)	406	406	406	406	406	406
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
HANDLEBAR (MM)	380/70	380/90	380/110	400/110	400/130	400/130
CRANKSET (MM)	160, 52-36T	165, 52-36T	165, 52-36T	170, 52-36T	170, 52-36T	170, 52-36T
SEATPOST (MM)	320	320	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RR 9.8

Matte Carbon / Black

CHF 4'999.–



FRAME SIZE	EAN	Quantity
490mm (XS)	8592842209755	
520mm (S)	8592842209762	
540mm (M)	8592842209779	
560mm (L)	8592842209786	
580mm (XL)	8592842209793	

SPECIFICATION

BASE INFO

WEIGHT	7.50 kg

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	BF-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible.
FORK	RR Mid Modulus Carbon Fork, Rake 50mm
BOTTOM BRACKET	SHIMANO BB-RS501, BSA, shell 68mm
HEADSET	ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	ONE, TA12x120, M12xP1.0x15L, Black
REAR AXLE	ONE, TA12x161, M12xP10x9.2mm, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO ULTEGRA R8170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO ULTEGRA R8170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO ULTEGRA FD-R8150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO ULTEGRA RD-R8150, Shadow Design
CRANKSET	SHIMANO ULTEGRA FC-R8100, Hollowtech II, 50-34T
CASSETTE	SHIMANO ULTEGRA CS-R8101, 12-speed, 11-34T
CHAIN	SHIMANO XT CN-M8100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL800, 160mm
BRAKE REAR	SHIMANO ULTEGRA R8170, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL800, 140mm

WHEELS

WHEELSET FRONT	DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x142mm, SH11, Tubeless Ready
TIRE FRONT	Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race
TIRE REAR	Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizi:k Vento Argo R5, Alloy
SEATPOST	ONE Carbon, Offset 13mm
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	74	74	70	70	70
SEAT TUBE LENGTH (MM)	471	486	503	522	533
EFFECTIVE TOP TUBE LENGTH (MM)	503	524	540	555	576
STACK HEIGHT (MM)	505	527	546	565	584
REACH (MM)	368	378	384	388	397
SEAT TUBE ANGLE	75°	74,5°	74°	73,5°	73°
HEAD TUBE ANGLE	71,5°	72,5°	73°	73°	73°
REAR CENTER (MM)	410	410	410	410	410
HEAD TUBE LENGTH (MM)	100	120	140	160	180
HANDLEBAR (MM)	380/70	380/90	400/100	400/100	420/100
CRANKSET (MM)	165	165	170	172.5	172.5
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RR 9.5

Matte Carbon / White

CHF 2'999.–



FRAME SIZE	EAN	Quantity
490mm (XS)	8592842210102	
520mm (S)	8592842210119	
540mm (M)	8592842210126	
560mm (L)	8592842210133	
580mm (XL)	8592842210140	

SPECIFICATION

BASE INFO

WEIGHT	8.45 kg

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	BF-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible.
FORK	RR Mid Modulus Carbon Fork, Rake 50mm
BOTTOM BRACKET	SHIMANO BB-RS501, BSA, shell 68mm
HEADSET	ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	ONE, TA12x120, M12xP1.0x15L, Black
REAR AXLE	ONE, TA12x161, M12xP1.0x9.2mm, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7170, Di2, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7170, Di2, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7150, Down Swing, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7150, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7101, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO 105 R7170, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO 105 R7170, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE FRONT	Schwalbe One Performance, RaceGuard, 28-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE REAR	Schwalbe One Performance, RaceGuard, 28-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Carbon, Offset 13mm
SEATPOST CLAMP	Frame Integrated Clamp

GEOMETRY

FRAME SIZE	490mm (XS)	520mm (S)	540mm (M)	560mm (L)	580mm (XL)
BB DROP (MM)	74	74	70	70	70
SEAT TUBE LENGTH (MM)	471	486	503	522	533
EFFECTIVE TOP TUBE LENGTH (MM)	503	524	540	555	576
STACK HEIGHT (MM)	505	527	546	565	584
REACH (MM)	368	378	384	388	397
SEAT TUBE ANGLE	75°	74,5°	74°	73,5°	73°
HEAD TUBE ANGLE	71,5°	72,5°	73°	73°	73°
REAR CENTER (MM)	410	410	410	410	410
HEAD TUBE LENGTH (MM)	100	120	140	160	180
STEM (MM)	80	80	90	100	110
HANDLEBAR (MM)	410	410	410	430	430
CRANKSET (MM)	165	165	170	172.5	172.5
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XR 6.5 GF

Gloss Black / White

CHF 1'799.–



FRAME SIZE	EAN	Quantity
470mm (XS)	8592842215053	
490mm (S)	8592842215060	
510mm (M)	8592842215077	
530mm (L)	8592842215084	
550mm (XL)	8592842215091	
580mm (XXL)	8592842215107	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguadrs ready
FORK	XR Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-313, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	SB02, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	SB02, TA12x165, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS LEFT	SHIMANO 105 R7120, 2-speed
SHIFTERS RIGHT	SHIMANO 105 R7120, 12-speed
FRONT DERAILLEUR	SHIMANO 105 FD-R7100, Down Swing, Down Pull, Brazed-On Type
REAR DERAILLEUR	SHIMANO 105 RD-R7100, Shadow Design
CRANKSET	SHIMANO 105 FC-R7100, Hollowtech II, 50-34T
CASSETTE	SHIMANO 105 CS-R7101, 12 speed, 11-34T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO 105 R7120, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO 105 R7120, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE FRONT	Schwalbe One Performance, RaceGuard, 30-622, ADDIX
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE REAR	Schwalbe One Performance, RaceGuard, 30-622, ADDIX
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Race, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	470mm (XS)	490mm (S)	510mm (M)	530mm (L)	550mm (XL)	580mm (XX
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	470	490	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	530	538	551	579	599	619
STACK HEIGHT (MM)	523	553	581	600	619	638
REACH (MM)	380	379	381	391	407	415
SEAT TUBE ANGLE	74°	74°	73.8°	72.6°	72.8°	72.3°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	425	425	425	425	425	425
HEAD TUBE LENGTH (MM)	100	130	160	180	200	220
WHEELBASE (MM)	1004	1009	1016	1033	1051	1065
STEM (MM)	70	80	100	100	110	110
HANDLEBAR (MM)	410	410	410	410	430	430
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/courtry



gravel

XR GR / GRA

Gravel ist kein Trend. Es ist die pure Freiheit auf zwei Rädern. Wenn der Asphalt aufhört, beginnt das Abenteuer! Ob die Jagd nach Sekunden im Rennen, Bikepacking auf endlosen Nebenstrassen oder die Feierabendrunde im Wald; Keine Grenzen, nur du, dein Superior Bike und die Leidenschaft für jeden Untergrund.

Le gravel, c'est la liberté pure sur deux roues. Quand l'asphalte s'arrête, l'aventure commence. Que ce soit en course, en bikepacking ou lors d'une sortie en forêt: aucune limite, juste toi, ton vélo Superior et la passion de tous les terrains.

XR 9.8 GR

Gloss Purple Carbon / Matte Carbon

CHF 4'899.–



FRAME SIZE	EAN	Quantity
XS		
S		
M	8592842224499	
L		
XL		
XXL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-502-03, Carbon XR Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, UDH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Mid Modulus Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-318R1S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings
FRONT AXLE	ZY-THA19A, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX825, Di2
REAR DERAILLEUR	SHIMANO GRX8
CRANKSET	SHIMANO GRX FC-RX820 Hollowtech II 44T
CASSETTE	SHIMANO GRX
CHAIN	SHIMANO XT CN M8100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX825, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL800, 160mm
BRAKE REAR	SHIMANO GRX RX825, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL800, 140mm

WHEELS

WHEELSET FRONT	DT Swiss GRC 1400 DICUT® CS, Carbon, CL, 12x100mm, Height 40mm, Tubeless Ready
WHEELSET REAR	DT Swiss GRC 1400 DICUT® CS, Carbon, CL, 12x142mm, SH13, Height 40mm, Tubeless Ready
TIRE FRONT	Schwalbe G-One RS PRO Evo, Super Race, V-Guard, TL-Ready, 45-622, ADDIX Race
TIRE REAR	Schwalbe G-One RS PRO Evo, Super Race, V-Guard, TL-Ready, 45-622, ADDIX Race

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Fizi:k Vento Argo R5, Alloy
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

CITY/ SUV SET

REAR LIGHT	Litemove Rear Visibility Light, Red

GEOMETRY

FRAME SIZE	XS	S	M	L	XL	XXL
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	420	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	526	536	546	570	592	611
STACK HEIGHT (MM)	525	545	563	582	601	620
REACH (MM)	380	379	381	391	407	414
SEAT TUBE ANGLE	74.7°	74°	73.7°	72.6°	72.9°	72°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	415	415	415	415	415	415
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
WHEELBASE (MM)	993	995	1000	1016	1034	1048
HANDLEBAR (MM)	380/70	380/70	420/90	420/90	440/100	440/100
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	320/0mm	320/0mm	400/15mm	400/15mm	400/15mm	400/15mm

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XR 9.5 GRA

Matte Black / Carbon

CHF 2'999.–



FRAME SIZE	EAN	Quantity
XS		
S		
M	8592842224512	
L		
XL		
XXL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-502-04, Carbon XR Adventure Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, UDH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
FORK	XR Adventure Mid Modulus Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-318R1, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	ZY-THA19A, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX715, Di2
REAR DERAILLEUR	SHIMANO GRX7
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO GRX
CHAIN	SHIMANO DEORE CN M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RS715/RX410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO GRX RX715/RX410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

WHEELSET FRONT	DT Swiss G 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss G 1800 SPLINE®, CL, 12x142mm, SH13, Tubeless Ready
TIRE FRONT	Schwalbe G-One RS Performance, RaceGuard, TL-Ready, 45-622, ADDIX Eco
TIRE REAR	Schwalbe G-One RS Performance, RaceGuard, TL-Ready, 45-622, ADDIX Eco

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, BB 31.8mm, Reach 70mm, Drop 120mm, Flare 8°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

CITY/ SUV SET

REAR LIGHT	Litemove Rear Visibility Light, Red

GEOMETRY

FRAME SIZE	XS	S	M	L	XL	XXL
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	420	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	526	536	546	570	592	611
STACK HEIGHT (MM)	525	545	563	582	601	620
REACH (MM)	380	379	381	391	407	414
SEAT TUBE ANGLE	74.7°	74°	73.7°	72.6°	72.9°	72°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	415	415	415	415	415	415
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
WHEELBASE (MM)	993	995	1000	1016	1034	1048
STEM (MM)	70	70	80	80	100	100
HANDLEBAR (MM)	400	400	400	420	420	420
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	320/0mm	320/0mm	400/15mm	400/15mm	400/15mm	400/15mm

XR 9.3 GRA

Matte Trooper Green

CHF 2'299.–



SPECIFICATION

BASE INFO

WEIGHT	9.75 kg

ISO AND EN NORM

LOAD CAPACITY	120 Kg
ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
FRONT AXLE	ZY-THA19A, TA12x119, M12xP1.5x8.5L, Black
FRAME	SU-502-04, Carbon XR Adventure Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, UDH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready.
HEADSET	ACROS AIX-318R1, ICR, OD56, IS52/28.6 - 40IPS
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black
FORK	XR Adventure Mid Modulus Carbon Fork

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-45T
CHAIN	SHIMANO DEORE CN-M6100
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design

BRAKING SYSTEM

ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
TIRE FRONT	Schwalbe G-One RS Performance, RaceGuard, TL-Ready, 45-622, ADDIX Eco
HUB REAR	SHIMANO FH-TC500-MS, 28H, CL, 12X142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
NIPPLES	SAPIM, Brass
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
SPOKES	SAPIM Race, Stainless Black
TIRE REAR	Schwalbe G-One Allround Performance, RaceGuard, TL-Ready, 45-622, ADDIX

COCKPIT

HANDLEBAR	ONE Alloy, BB 31.8mm, Reach 70mm, Drop 120mm, Flare 8°
STEM	ONE Race ICR, Alloy, 31,8mm, -7°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Aero Carbon
SEATPOST CLAMP	Frame Integrated Clamp

CITY/ SUV SET

REAR LIGHT	Litemove Rear Visibility Light, Red

GEOMETRY

FRAME SIZE	XS	S	M	L	XL	XXL
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	420	462	482	502	522	552
EFFECTIVE TOP TUBE LENGTH (MM)	526	536	546	570	592	611
STACK HEIGHT (MM)	525	545	563	582	601	620
REACH (MM)	380	379	381	391	407	414
SEAT TUBE ANGLE	74.7°	74°	73.7°	72.6°	72.9°	72°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	415	415	415	415	415	415
HEAD TUBE LENGTH (MM)	100	120	140	160	180	200
WHEELBASE (MM)	993	995	1000	1016	1034	1048
STEM (MM)	70	70	80	80	100	100
HANDLEBAR (MM)	400	400	400	420	420	420
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	320/0mm	320/0mm	400/15mm	400/15mm	400/15mm	400/15mm

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XR 6.5 GRA

Brush Alu

CHF 1'699.–



FRAME SIZE	EAN	Quantity
XS		
S		
M	8592842224543	
L		
XL		
XXL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguadrs ready
FORK	XR Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-318R1, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	ZY-THA19A, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	ZY-THA19A, TA12x165, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-45T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT70, 160mm
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT70, 140mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE FRONT	Schwalbe G-One Comp Active Line, K-Guard, 45-622, Green Compound, 50EPI
HUB REAR	SHIMANO FH-TC500-MS, 28H, CL, 12X142mm, THRU Type AXLE
RIM REAR	DT Swiss R500, Disc, 28H, Tubeless Ready
TIRE REAR	Schwalbe G-One Comp Active Line, K-Guard, 45-622, Green Compound, 50EPI
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, BB 31.8mm, Reach 70mm, Drop 120mm, Flare 8°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1332, 31.8mm, Black

GEOMETRY

FRAME SIZE	XS	S	M	L	XL	XXL
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	470	490	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	530	538	551	579	599	619
STACK HEIGHT (MM)	523	553	581	600	619	638
REACH (MM)	380	379	381	391	407	415
SEAT TUBE ANGLE	74°	74°	73.8°	72.6°	72.8°	72.3°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	425	425	425	425	425	425
HEAD TUBE LENGTH (MM)	100	130	160	180	200	220
WHEELBASE (MM)	1004	1009	1016	1033	1051	1065
STEM (MM)	70	70	80	80	100	100
HANDLEBAR (MM)	400	400	400	420	420	420
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XR 6.3 GRA

Gloss Mist Green / Trooper Green

CHF 1'449.–



FRAME SIZE	EAN	Quantity
XS		
S		
M		
L		
XL		
XXL		

SPECIFICATION

BASE INFO

WEIGHT	11.05 kg

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguadrs ready
FORK	XR Carbon Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-318R1, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	ZY-THA19A, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	ZY-THA19A, TA12x165, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES U6030, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6030, 42T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO CUES U6030, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 160mm
BRAKE REAR	SHIMANO CUES U6030, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	STARS J21DC, Disc, 28H
TIRE FRONT	Schwalbe G-One Comp Active Line, K-Guard, 45-622, Green Compound, 50EPI
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	STARS J21DC, Disc, 28H
TIRE REAR	Schwalbe G-One Comp Active Line, K-Guard, 45-622, Green Compound, 50EPI
SPOKES	SAPIM Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, BB 31.8mm, Reach 70mm, Drop 120mm, Flare 8°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1332, 31.8mm, Black

GEOMETRY

FRAME SIZE	XS	S	M	L	XL	XXL
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	470	490	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	530	538	551	579	599	619
STACK HEIGHT (MM)	523	553	581	600	619	638
REACH (MM)	380	379	381	391	407	415
SEAT TUBE ANGLE	74°	74°	73.8°	72.6°	72.8°	72.3°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	425	425	425	425	425	425
HEAD TUBE LENGTH (MM)	100	130	160	180	200	220
WHEELBASE (MM)	1004	1009	1016	1033	1051	1065
HANDLEBAR (MM)	400	400	400	420	420	420
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XR 6.2 GRA

Brush Alu

CHF 1'349.–



FRAME SIZE	EAN	Quantity
XS		
S		
M		
L		
XL		
XXL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguadrs ready
FORK	XR Alloy Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-318R1, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	ZY-THA19A, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	ZY-THA19A, TA12x165, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES U6030, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6030, 42T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO CUES U6030, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 160mm
BRAKE REAR	SHIMANO CUES U6030, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	STARS J21DC, Disc, 28H
TIRE FRONT	Schwalbe G-One Comp Active Line, K-Guard, 45-622, Green Compound, 50EPI
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	STARS J21DC, Disc, 28H
TIRE REAR	Schwalbe G-One Comp Active Line, K-Guard, 45-622, Green Compound, 50EPI
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, BB 31.8mm, Reach 70mm, Drop 120mm, Flare 8°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1332, 31.8mm, Black

GEOMETRY

FRAME SIZE	XS	S	M	L	XL	XXL
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	470	490	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	530	538	551	579	599	619
STACK HEIGHT (MM)	523	553	581	600	619	638
REACH (MM)	380	379	381	391	407	415
SEAT TUBE ANGLE	74°	74°	73.8°	72.6°	72.8°	72.3°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	425	425	425	425	425	425
HEAD TUBE LENGTH (MM)	100	130	160	180	200	220
WHEELBASE (MM)	1004	1009	1016	1033	1051	1065
HANDLEBAR (MM)	400	400	400	420	420	420
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XR 6.2 GRA

Gloss Off White

CHF 1'349.–



FRAME SIZE	EAN	Quantity
XS		
S		
M		
L		
XL		
XXL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguadrs ready
FORK	XR Alloy Fork
BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
HEADSET	ACROS AIX-318R1, ICR, OD56, IS52/28.6 - 40IPS
FRONT AXLE	ZY-THA19A, TA12x119, M12xP1.5x8.5L, Black
REAR AXLE	ZY-THA19A, TA12x165, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES U6030, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6030, 42T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO CUES U6030, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 160mm
BRAKE REAR	SHIMANO CUES U6030, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE
RIM FRONT	STARS J21DC, Disc, 28H
TIRE FRONT	Schwalbe G-One Comp Active Line, K-Guard, 45-622, Green Compound, 50EPI
HUB REAR	SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE
RIM REAR	STARS J21DC, Disc, 28H
TIRE REAR	Schwalbe G-One Comp Active Line, K-Guard, 45-622, Green Compound, 50EPI
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, BB 31.8mm, Reach 70mm, Drop 120mm, Flare 8°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1332, 31.8mm, Black

GEOMETRY

FRAME SIZE	XS	S	M	L	XL	XXL
BB DROP (MM)	77	77	75	75	73	73
SEAT TUBE LENGTH (MM)	470	490	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	530	538	551	579	599	619
STACK HEIGHT (MM)	523	553	581	600	619	638
REACH (MM)	380	379	381	391	407	415
SEAT TUBE ANGLE	74°	74°	73.8°	72.6°	72.8°	72.3°
HEAD TUBE ANGLE	70.5°	71°	71.5°	71.5°	72°	72°
REAR CENTER (MM)	425	425	425	425	425	425
HEAD TUBE LENGTH (MM)	100	130	160	180	200	220
WHEELBASE (MM)	1004	1009	1016	1033	1051	1065
HANDLEBAR (MM)	400	400	400	420	420	420
CRANKSET (MM)	165	165	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

the future is BIG



gravel 32“

XR GRA 32

Im Jahr 2004 war Superior eine der ersten Marken weltweit, die auf 29»Räder setzte. Damals hielten das viele für verrückt. Zu groß. Zu anders. Zu früh. Wir haben ihnen das Gegenteil bewiesen. Jetzt verschieben wir erneut die Grenzen.Unser überzeugter Ride in die Zukunft sind 32» Gravelbikes! Größerer Durchmesser. Mehr Geschwindigkeit. Mehr Flow. Mehr Möglichkeiten.Das Gefühl nach der Fahrt – Gravel nur schneller!

En 2004, Superior a été l’une des premières marques au monde à miser sur les roues de 29 pouces. À l’époque, beaucoup pensaient que c’était une folie. Trop grand. Trop différent. Trop tôt. Nous leur avons prouvé le contraire. Aujourd’hui, nous repoussons à nouveau les limites. Notre vision de l’avenir: les gravel bikes de 32 pouces! Un diamètre plus grand. Plus de vitesse. Plus de fluidité. Plus de possibilités. La sensation après la sortie: le gravel, mais en plus rapide!

XR 6.7 GRA 32

Brush Alu

CHF 2'899.–



FRAME SIZE	EAN	Quantity
32" (M)	8592842230636	
32" (L)	8592842231343	
32" (XL)	8592842230629	
32" (XXL)	8592842231350	

SPECIFICATION

ISO AND EN NORM

LOAD CAPACITY	120 Kg
ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
FRONT AXLE	ZY-THA19A, TA12x129, M12xP1.5x8.5L, Black
FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguadrs ready
HEADSET	ACROS AIX-318R1, ICR, OD56, IS52/28.6 - 40IPS
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black
FORK	XR 32" Carbon Fork

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX715, Di2
REAR DERAILLEUR	SHIMANO GRX7 RD-X7050, Shadow Plus Design, 13-speed
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO GRX CS-HG820-13, 13-speed, 10-48T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

ROTOR FRONT	SHIMANO RT-CL700, 180mm
BRAKE FRONT	SHIMANO GRX RS715/RX410, hydraulic disc brake
BRAKE REAR	SHIMANO GRX RX715/RX410, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL700, 160mm

WHEELS

WHEELSET FRONT	DT Swiss GRC ELEMENT DICUT®, Carbon, CL, 12x110mm, Height 40mm, Tubeless Ready
WHEELSET REAR	DT Swiss GRC ELEMENT DICUT®, Carbon, CL, 12x148mm, SH13, Height 40mm, Tubeless Ready
TIRE FRONT	Schwalbe G-One RX PRO, V-Guard, TL-Ready, 50-686, ADDIX Race
TIRE REAR	Schwalbe G-One RX PRO, V-Guard, TL-Ready, 50-686, ADDIX Race

COCKPIT

HANDLEBAR	ONE Alloy, BB 31.8mm, Reach 70mm, Drop 120mm, Flare 8°
GRIPS LEFT	ONE Handlebar Tape
STEM	ONE Race ICR, Alloy, 31,8mm, -7°

PARTS

SEATPOST CLAMP	ONE ZY-SC1332, 31.8mm, Black
SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE, Alloy, 27.2mm

GEOMETRY

FRAME SIZE	32" (M)	32" (L)	32" (XL)	32" (XXL)
BB DROP (MM)	110	110	110	110
SEAT TUBE LENGTH (MM)	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	558	581	600	620
STACK HEIGHT (MM)	600	602	623	634
REACH (MM)	407	425	438	456
SEAT TUBE ANGLE	73.7°	73.5°	73.5°	73.5°
HEAD TUBE ANGLE	69.5°	70°	70.5°	71°
REAR CENTER (MM)	465	465	465	465
HEAD TUBE LENGTH (MM)	100	100	120	130
WHEELBASE (MM)	1088	1104	1120	1136
STEM (MM)	80	80	100	100
HANDLEBAR (MM)	400	420	420	420
CRANKSET (MM)	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XR 6.5 GRA 32

Brush Alu

CHF 1'899.–



SPECIFICATION

ISO AND EN NORM

LOAD CAPACITY	120 Kg
ISO norm	ISO 4210-2 Road Racing bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

BOTTOM BRACKET	SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm
FRONT AXLE	ZY-THA19A, TA12x129, M12xP1.5x8.5L, Black
FRAME	Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguadrs ready
HEADSET	ACROS AIX-318R1, ICR, OD56, IS52/28.6 - 40IPS
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black
FORK	XR 32" Carbon Fork

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	SHIMANO GRX FC-RX610, 40T
CASSETTE	SHIMANO DEORE CS-M6200, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

ROTOR FRONT	SHIMANO RT-CL700, 180mm
BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL700, 160mm

WHEELS

WHEELSET FRONT	DT Swiss GR LN CLASIC®, CL, 12x110mm, Height 30mm, Tubeless Ready
WHEELSET REAR	DT Swiss GR LN CLASIC®, CL, 12x148mm, SH12, Height 30mm, Tubeless Ready
TIRE FRONT	Schwalbe G-One RX PRO, V-Guard, TL-Ready, 50-686, ADDIX Race
TIRE REAR	Schwalbe G-One RX PRO, V-Guard, TL-Ready, 50-686, ADDIX Race

COCKPIT

HANDLEBAR	ONE Alloy, BB 31.8mm, Reach 70mm, Drop 120mm, Flare 8°
GRIPS LEFT	ONE Handlebar Tape
STEM	ONE Race ICR, Alloy, 31,8mm, -7°

PARTS

SEATPOST CLAMP	ONE ZY-SC1332, 31.8mm, Black
SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE, Alloy, 27.2mm

GEOMETRY

FRAME SIZE	32" (M)	32" (L)	32" (XL)	32" (XXL)
BB DROP (MM)	110	110	110	110
SEAT TUBE LENGTH (MM)	510	530	550	580
EFFECTIVE TOP TUBE LENGTH (MM)	558	581	600	620
STACK HEIGHT (MM)	600	602	623	634
REACH (MM)	407	425	438	456
SEAT TUBE ANGLE	73.7°	73.5°	73.5°	73.5°
HEAD TUBE ANGLE	69.5°	70°	70.5°	71°
REAR CENTER (MM)	465	465	465	465
HEAD TUBE LENGTH (MM)	100	100	120	130
WHEELBASE (MM)	1088	1104	1120	1136
STEM (MM)	80	80	100	100
HANDLEBAR (MM)	400	420	420	420
CRANKSET (MM)	170	172.5	172.5	175
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country



e-gravel

iXR

E-Gravel ist die ultimative Freiheit, noch weiter zu fahren. Vergiss die Frage wie steil der Schotterpass wird oder wie weit der Weg noch ist. Mit dem Extra-Schub deines Superior E-Gravelbikes erlebst Du epische Gravel-Abenteuer intensiver denn je!

L'E-Gravel, c'est la liberté ultime d'aller encore plus loin. Oublie les pentes raides et les longues distances. Grâce à l'assistance de ton E-Gravel Superior, chaque aventure devient encore plus intense!

iXR 6.5

Gloss Dust

CHF 3'999.–



FRAME SIZE	EAN	Quantity
XS	8592842216227	
S	8592842216234	
M	8592842216241	
L	8592842216258	
XL	8592842216265	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH SX Performance, Battery CompactTube 400Wh, Smart System
MAX. TORQUE	60Nm / 400%
SUPPORT UP TO SPEED	25km/h
WEIGHT	17.25 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance SX, 55Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH CompactTube, 400Wh
DISPLAY	BOSCH Mini Remote, Drop Bar

FRAMESET

FRAME	SU-E50-01, Alloy double-butted , Gravel Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, UDH dropout, Integrated Cable Routing, Bike packing and mudguards ready
SUSPENSION FORK	RockShox RUDY Base, Tapered, SoloAir, 12x100mm axle, 40mm travel
HEADSET	ACROS AZX-327R1S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings
REAR AXLE	SB02, TA12x165, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO GRX RX610, 12-speed
REAR DERAILLEUR	SHIMANO GRX RD-RX822, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T
CASSETTE	SHIMANO SLX CS-M7101, 12-speed, 10-45T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO GRX RX610, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 160mm
BRAKE REAR	SHIMANO GRX RX610, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 160mm

WHEELS

WHEELSET FRONT	DT Swiss HG 1800 SPLINE®, CL, 12x100mm, Tubeless Ready
WHEELSET REAR	DT Swiss HG 1800 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready
TIRE FRONT	**ONE Alloy, BB 31.8mm, Reach 70mm, Drop 120mm, Flare 8°**
TIRE REAR	Schwalbe G-One Allround Performance, RaceGuard, TL-Ready, 45-622, ADDIX

COCKPIT

STEM	ONE Race ICR, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Flare 2°, Backsweep 6°
GRIPS LEFT	ONE Handlebar Tape

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE Sport, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	XS	S	M	L	XL
BB DROP (MM)	70	70	70	70	70
SEAT TUBE LENGTH (MM)	470	490	510	530	550
EFFECTIVE TOP TUBE LENGTH (MM)	530	540	550	570	590
STACK HEIGHT (MM)	553	564	574	595	616
REACH (MM)	377	378	380	394	402
SEAT TUBE ANGLE	74,5°	74°	73,5°	73,5°	73°
HEAD TUBE ANGLE	70°	70,5°	70,5°	71°	71,5°
REAR CENTER (MM)	445	445	445	445	445
HEAD TUBE LENGTH (MM)	110	120	130	150	170
WHEELBASE (MM)	1039	1040	1045	1045	1070
STEM (MM)	80	80	90	100	110
HANDLEBAR (MM)	410	410	410	430	430
CRANKSET (MM)	165	165	170	170	170
SEATPOST (MM)	350	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country



e-MTB Fully

eXF



Unsere vollgefederten E-MTBs garantieren maximalen Spass auf den Trails. Dank ausdauernder 800Wh Akkus und dem kraftvollen Bosch Performance CX Motor meisterst du selbst steilste Rampen mühelos. Und das Beste: Für den Alltag und maximale Vielseitigkeit ist das Bike auch in der vollausgestatteten SUV-Variante erhältlich. Keine Kompromisse, kein Limit – einfach purer Fahrspass bei jeder Tour.

Nos VTT électriques tout suspendus garantissent un maximum de plaisir sur les trails. Grâce à leur batterie endurante de 800 Wh et au puissant moteur Bosch Performance CX, même les montées les plus raides deviennent faciles. Pour le quotidien et une polyvalence maximale, le vélo est aussi disponible en version SUV entièrement équipée. Aucun compromis, aucune limite: le pur plaisir de rouler à chaque sortie.

eXF 6.2

Gloss Chalk Grey

CHF 4‘299.–



FRAME SIZE	EAN	Quantity
S		
M		
L		
XL		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 800Wh, Smart System
DISTANCE	140km
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 100Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH LED Controller

FRAMESET

FRAME	SU-E300-02, Alu X6 Ultralite MTB Trail SU-E-300-02, Advanced e-MTB Geometry, Travel 140 mm, BOSCH CX Performance 5G ready, Integrated 800Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	SR Suntour XCR36X, Air, Tapered, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select, size 230x57.5mm
HEADSET	ACROS AZX-327R1, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	FSA CK-745/IS, Alloy, Black
CHAINRING	FSA, 34T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 203MM
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, Tubeless, 32H
TIRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, Tubeless, 32H
TIRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 18mm rise, back sweep 9°, 35mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST CLAMP	ONE ZY-SC1735, 34.9mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	S	M	L	XL
BB DROP (MM)	20	20	20	20
SEAT TUBE LENGTH (MM)	400	443	480	520
EFFECTIVE TOP TUBE LENGTH (MM)	605	620	646	672
STACK HEIGHT (MM)	622	622	626	631
REACH (MM)	445	460	485	510
SEAT TUBE ANGLE	71°	71°	71°	71°
HEAD TUBE ANGLE	64°	64°	64°	64°
REAR CENTER (MM)	467	467	467	467
HEAD TUBE LENGTH (MM)	130	130	135	140
WHEELBASE (MM)	1252	1267	1294	1321
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	165

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

eXF 6.2 SUV

Gloss Chalk Grey

CHF 4‘399.–



FRAME SIZE	EAN	Quantity
S		
M		
L		
XL		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 800Wh, Smart System
DISTANCE	140km
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 100Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH LED Controller

FRAMESET

FRAME	SU-E300-02, Alu X6 Ultralite MTB Trail SU-E-300-02, Advanced e-MTB Geometry, Travel 140 mm, BOSCH CX Performance 5G ready, Integrated 800Wh battery, 3D alloy one piece link, Alloy swingarm, Boost 12x148 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	SR Suntour XCR36X, Air, Tapered, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select, size 230x57.5mm
HEADSET	ACROS AZX-327R1, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	FSA CK-745/IS, Alloy, Black
CHAINRING	FSA, 38T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 203MM
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, Tubeless, 32H
TIRE FRONT	Schwalbe Johnny Watts Performance, RaceGuard, 29x2.35", ADDIX
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, Tubeless, 32H
TIRE REAR	Schwalbe Johnny Watts Performance, RaceGuard, 29x2.35", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, 0°
HANDLEBAR	ONE Alloy, 20mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST CLAMP	ONE ZY-SC1735, 34.9mm, with Quick Release level, Black

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	S	M	L	XL
BB DROP (MM)	20	20	20	20
SEAT TUBE LENGTH (MM)	400	443	480	520
EFFECTIVE TOP TUBE LENGTH (MM)	605	620	646	672
STACK HEIGHT (MM)	622	622	626	631
REACH (MM)	445	460	485	510
SEAT TUBE ANGLE	71°	71°	71°	71°
HEAD TUBE ANGLE	64°	64°	64°	64°
REAR CENTER (MM)	467	467	467	467
HEAD TUBE LENGTH (MM)	130	130	135	140
WHEELBASE (MM)	1252	1267	1294	1321
STEM (MM)	60	60	60	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	165

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

e-MTB hardtail

eXP



Unsere E-MTB Hardtails garantieren maximalen Spass auf Feldwegen, Schotter und Trails. Und das Beste: Für deinen Alltag und maximale Vielseitigkeit ist das Bike auch in der vollausgestatteten SUV-Variante erhältlich. Mach keine Kompromisse, erlebe grenzenlose Freiheit und puren Fahrspaß auf jedem Kilometer.

Nos VTT électriques semi-rigides garantissent un maximum de plaisir sur les chemins, le gravel et les trails. Pour le quotidien et une polyvalence maximale, le vélo est aussi disponible en version SUV entièrement équipée. Aucun compromis: profite d'une liberté sans limites et d'un pur plaisir de rouler à chaque kilomètre.

eXP 6.4

Gloss Silver Grey

CHF 3'199.–



FRAME SIZE	EAN	Quantity
S		
M		
L		
XL		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 800Wh, Smart System
DISTANCE	200km
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 100Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH LED Controller

FRAMESET

FRAME	SU-E40-03, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	SR Suntour XCM32, Tapered, Air, Lock Out, 15x110mm axle, 120mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartrige, Tapered
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6001-10R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	FSA CK-745/IS, Alloy, Black
CHAINRING	FSA, 34T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +3°
HANDLEBAR	ONE Alloy, 20mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1735, 34.9mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	S	M	L	XL
BB DROP (MM)	56	56	56	56
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	581	606	626	652
STACK HEIGHT (MM)	638	638	638	667
REACH (MM)	445	459	479	500
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1207	1221	1241	1270
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	165
SEATPOST (MM)	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

eXP 6.4 SUV

Matte Olive Green

CHF 3'399.–



FRAME SIZE	EAN	Quantity
S		
M		
L		
XL		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 800Wh, Smart System
DISTANCE	200km
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 100Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH LED Controller

FRAMESET

FRAME	SU-E40-03, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	SR Suntour XCM32, Tapered, Air, Lock Out, 15x110mm axle, 120mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartrige, Tapered
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6001-10R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	FSA CK-745/IS, Alloy, Black
CHAINRING	FSA, 38T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +7°
HANDLEBAR	ONE Alloy, 20mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1735, 34.9mm, with Quick Release level, Black

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	S	M	L	XL
BB DROP (MM)	56	56	56	56
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	581	606	626	652
STACK HEIGHT (MM)	638	638	638	667
REACH (MM)	445	459	479	500
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1207	1221	1241	1270
STEM (MM)	60	60	60	60
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	165
SEATPOST (MM)	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

eXP 6.4 LS SUV

Matte Olive Green

CHF 3'399.–



FRAME SIZE	EAN	Quantity
29" (S)		
29" (M)		
29" (L)		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 800Wh, Smart System
DISTANCE	200km
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 100Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH LED Controller

FRAMESET

FRAME	SU-E40-05, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	SR Suntour XCM32, Tapered, Air, Lock Out, 15x110mm axle, 100mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartrige, Tapered
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6001-10R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	FSA CK-745/IS, Alloy, Black
CHAINRING	FSA, 38T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +7°
HANDLEBAR	ONE Alloy, 20mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1735, 34.9mm, with Quick Release level, Black

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	29" (S)	29" (M)	29" (L)
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	381	457	510
EFFECTIVE TOP TUBE LENGTH (MM)	618	638	667
STACK HEIGHT (MM)	654	654	654
REACH (MM)	430	450	479
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°
REAR CENTER (MM)	450	450	450
HEAD TUBE LENGTH (MM)	140	140	140
WHEELBASE (MM)	1153	1173	1202
STEM (MM)	60	60	60
HANDLEBAR (MM)	760	760	760
CRANKSET (MM)	165	165	165
SEATPOST (MM)	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

eXP 6.3

Gloss Metallic Black

CHF 2'999.–



FRAME SIZE	EAN	Quantity
S		
M		
L		
XL		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH PX Performance, Battery PowerTube 600Wh, Smart System
DISTANCE	140km
MAX. TORQUE	90Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance PX, 90Nm, 2-bolt, BES3, generation 5
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH LED Controller

FRAMESET

FRAME	SU-E40-03, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	SR Suntour XCM32, Tapered, Air, Lock Out, 15x110mm axle, 120mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartrige, Tapered
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6001-10R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	FSA CK-745/IS, Alloy, Black
CHAINRING	FSA, 34T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +3°
HANDLEBAR	ONE Alloy, 20mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1735, 34.9mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	S	M	L	XL
BB DROP (MM)	56	56	56	56
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	581	606	626	652
STACK HEIGHT (MM)	638	638	638	667
REACH (MM)	445	459	479	500
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1207	1221	1241	1270
STEM (MM)	45	45	45	45
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	165	165	165	165
SEATPOST (MM)	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country



e-TOUR

eBLOX



Die Superior eBLOX E-Bikes verbinden Komfort, Stil und elektrische Leichtigkeit. Herzstück ist die bewährte, kraftvolle Bosch-Technologie, die dir eine souveräne Reichweite auf all deinen Wegen garantiert. Das klare, urbane Design sorgt für einen eleganten Auftritt in der City, während die entspannte Geometrie jede Fahrt – vom täglichen Arbeitsweg bis zum spontanen Wochenendausflug ins Grüne – in pure Entspannung verwandelt.

Les vélos électriques Superior eBLOX allient confort, style et légèreté électrique. Au cœur du système, la technologie Bosch éprouvée et puissante garantit une autonomie fiable sur tous tes trajets. Le design urbain épuré assure une allure élégante en ville, tandis que la géométrie confortable transforme chaque sortie, du trajet quotidien à l'escapade spontanée du week-end, en un pur moment de détente.

eBLOX 6.5

Matte Dark Chrome / Black

CHF 3'999.–



FRAME SIZE	EAN	Quantity
15,5" (S)	8592842216432	
17,5" (M)	8592842216449	
19" (L)	8592842216456	
21" (XL)	8592842216463	

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube Smart System
DISTANCE	200km
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 85Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH Kiox 300

FRAMESET

FRAME	SU-E40-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing
SUSPENSION FORK	RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604R1, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	SB02, TA12x171.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U8020, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CHAINRING	ONE Race, 38T, with Chain Guard
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Big Apple Performance, RaceGuard, 55-622
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Big Apple Performance, RaceGuard, 55-622
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30.9mm
SEATPOST CLAMP	ONE CC-610, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	spanninga Pling XDS
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	15,5" (S)	17,5" (M)	19" (L)	21" (XL)
BB DROP (MM)	51	51	51	51
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	592	612	632	642
STACK HEIGHT (MM)	638	638	638	656
REACH (MM)	460	459	479	50
SEAT TUBE ANGLE	78°	77°	77°	78°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	442	442	442	442
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1195	1215	1235	1264
STEM (MM)	65	65	65	90
HANDLEBAR (MM)	700	700	700	700
CRANKSET (MM)	160	160	160	160
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

eBLOX 6.4 LS

Gloss Rose Gold

CHF 3'699.–



FRAME SIZE	EAN	Quantity
27.5" (S)		
27.5" (M)		
29" (M)		
29" (L)		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 800Wh, Smart System
DISTANCE	150km
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 100Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH Purion 200

FRAMESET

FRAME	SU-E40-08, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	SR Suntour XCM32, Tapered, Air, Lock Out, 15x110mm axle, 100mm travel
HEADSET	ACROS AZF-604R1, ZS56/28.6 - ZS56/40, BlockLock 120°
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6001-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U8020, Shadow Plus Design
CRANKSET	FSA CK-745/IS, Alloy, Black
CHAINRING	FSA, 38T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO SM-RT10, 180mm
ROTOR FRONT	SHIMANO MT220, hydraulic disc brake
BRAKE REAR	SHIMANO SM-RT10, 180mm
ROTOR REAR	SHIMANO MT220, hydraulic disc brake

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Motion Big Apple, K-Guard, TwinSkin, 60-584
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Motion Big Apple, K-Guard, TwinSkin, 60-584
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder
HANDLEBAR	ONE Alloy, 30mm rise, back sweep 25°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1735, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	Spanninga NEOS 65, including day running light
REAR LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	27.5" (S)	27.5" (M)	29" (M)	29" (L)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	400	450	457	510
EFFECTIVE TOP TUBE LENGTH (MM)	604	634	643	672
STACK HEIGHT (MM)	641	641	674	674
REACH (MM)	420	450	450	479
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°
REAR CENTER (MM)	478	478	478	478
HEAD TUBE LENGTH (MM)	155	155	155	155
WHEELBASE (MM)	1164	1194	1181	1210
STEM (MM)	65	65	65	65
CRANKSET (MM)	165	165	165	165
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

eBLOX 6.2

Matte Titanium Chrome

CHF 2'999.–



FRAME SIZE	EAN	Quantity
S		
M		
L		
XL		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 600Wh, Smart System
DISTANCE	120km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line, 75Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH Purion 200

FRAMESET

FRAME	SU-E40-03, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	SR Suntour XCM32, Tapered, Air, Lock Out, 15x110mm axle, 100mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartrige, Tapered
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4001-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	FSA CK-745/IS, Alloy, Black
CHAINRING	FSA, 38T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Motion Big Apple, K-Guard, TwinSkin, 55-622
HUB REAR	SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Motion Big Apple, K-Guard, TwinSkin, 55-622
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, back sweep 25°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1735, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	S	M	L	XL
BB DROP (MM)	56	56	56	56
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	581	606	626	652
STACK HEIGHT (MM)	638	638	638	667
REACH (MM)	445	459	479	500
SEAT TUBE ANGLE	78°	77°	77°	77°
HEAD TUBE ANGLE	66°	66°	66°	66°
REAR CENTER (MM)	450	450	450	450
HEAD TUBE LENGTH (MM)	120	120	120	140
WHEELBASE (MM)	1207	1221	1241	1270
CRANKSET (MM)	165	165	165	165
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

eBLOX 6.2 LS

Gloss Metallic Black

CHF 2'999.–



FRAME SIZE	EAN	Quantity
27.5" (S)		
27.5" (M)		
29" (M)		
29" (L)		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 600Wh, Smart System
DISTANCE	120km
MAX. TORQUE	75Nm / 300%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line, 75Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 600Wh
DISPLAY	BOSCH Purion 200

FRAMESET

FRAME	SU-E40-08, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready
SUSPENSION FORK	SR Suntour XCM32, Tapered, Air, Lock Out, 15x110mm axle, 100mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartrige, Tapered
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4001-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	FSA CK-745/IS, Alloy, Black
CHAINRING	FSA, 38T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J30D, Disc, 32H
TIRE FRONT	Schwalbe Motion Big Apple, K-Guard, TwinSkin, 60-584
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J30D, Disc, 32H
TIRE REAR	Schwalbe Motion Big Apple, K-Guard, TwinSkin, 60-584
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, back sweep 25°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, Suspension, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1735, 34.9mm, with Quick Release level, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	HERRMANS H-Black MR8 E, 180lm
REAR LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
FENDER	Alloy
CARRIER	Atran Velo System

GEOMETRY

FRAME SIZE	27.5" (S)	27.5" (M)	29" (M)	29" (L)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	400	450	457	510
EFFECTIVE TOP TUBE LENGTH (MM)	604	634	643	672
STACK HEIGHT (MM)	641	641	674	674
REACH (MM)	420	450	450	479
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	69°	69°	69°	69°
REAR CENTER (MM)	478	478	478	478
HEAD TUBE LENGTH (MM)	155	155	155	155
WHEELBASE (MM)	1164	1194	1181	1210
CRANKSET (MM)	165	165	165	165
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

city e-bikes

eFARAD



Die City-E-Bikes von Superior machen alltägliche Fahrten zu einem stilvollen Erlebnis. Mit Bosch-Motoren, einer auf Komfort ausgelegten Geometrie und intelligenten Funktionen bieten sie eine leise, sanfte und unbeschwerte Art, sich durch die Stadt zu bewegen. Perfekt für den Weg zur Arbeit, Besorgungen oder entspannte Ausflüge.

Les vélos électriques urbains Superior transforment les trajets quotidiens en une expérience élégante. Avec leurs moteurs Bosch, leur géométrie confortable et leurs fonctions intelligentes, ils offrent une conduite silencieuse, fluide et sans effort en ville. Parfaits pour aller au travail, faire ses courses ou profiter d'une balade détendue.

eFARAD 6.9

Matte Anthracite / Matte Black

CHF 3‘599.–



FRAME SIZE	EAN	Quantity
460mm (S)		
500mm (M)		
540mm (L)		
580mm (XL)		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH CX Performance, Battery PowerTube 800Wh, Smart System
MAX. TORQUE	100Nm / 400%
SUPPORT UP TO SPEED	25km/h
WEIGHT	31.00 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain groundt contact (City and Urban bikes)
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance CX, 100Nm
CHARGER	BOSCH 4A
BATTERY	BOSCH PowerTube, 800Wh
DISPLAY	BOSCH PURION 200

FRAMESET

FRAME	Alloy, easy entry, integrated battery
SUSPENSION FORK	Suntour NVX32-5TA-LO-DS-700C-50, with lock-out, travel 50 mm, fork length 476 mm
HEADSET	ONE PT-1866A-078-1, 1-1/8"-1.5", ID52, Integrated

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-10R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	Alloy, ISIS, 170 mm
CHAINRING	42T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB REAR	SHIMANO FH-QC400, 36H, CL, QR Type
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass
RIMS	STARS J25D, Disc, Alloy, 36H
TIRES	Scalato Mondano, 55-622, with puncture protection

COCKPIT

STEM	ONE, Alloy, 31,8mm, ext. 90, adjustable
HANDLEBAR	Alloy, 31.8 x 660 mm
GRIPS LEFT	HERRMANS Altro, ergonomic
GRIPS RIGHT	HERRMANS Altro, ergonomic

PARTS

SADDLE	Selle Royal Explora
SEATPOST	ONE, Alloy, Suspension, 30.9mm

CITY/ SUV SET

FRONT LIGHT	Spanninga NEOS 65, including day running light
REAR LIGHT	Spanninga Pling XE
FENDER	Alloy, extrusion
CARRIER	alloy with MIK HD
FRAME LOCK	AXA Atlas including battery lock

GEOMETRY

FRAME SIZE	460mm (S)	500mm (M)	540mm (L)	580mm (XL)
BB DROP (MM)	75	75	75	75
SEAT TUBE LENGTH (MM)	460	500	540	580
EFFECTIVE TOP TUBE LENGTH (MM)	594	604	619	629
STACK HEIGHT (MM)	663	663	663	663
REACH (MM)	379	379	404	404
SEAT TUBE ANGLE	72°	71°	72°	71°
HEAD TUBE ANGLE	70°	70°	70°	70°
REAR CENTER (MM)	490	490	490	490
HEAD TUBE LENGTH (MM)	175	175	175	175
WHEELBASE (MM)	1125	1125	1150	1150
STEM (MM)	90	90	90	90
CRANKSET (MM)	170	170	170	170
SEATPOST (MM)		350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

eFARAD 6.7

Gloss Aubergine / Matte Aubergine

CHF 3'799.–



FRAME SIZE	EAN	Quantity
460mm (S)		
500mm (M)		
540mm (L)		
580mm (XL)		

SPECIFICATION

BASE INFO

MAX. TORQUE	90Nm / 400%
SUPPORT UP TO SPEED	25km/h

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain groundt contact (City and Urban bikes)
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance PX, 90Nm, 2-bolt, BES3, generation 5
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 720Wh
DISPLAY	BOSCH PURION 200

FRAMESET

FRAME	Alloy, easy entry, integrated battery
SUSPENSION FORK	Suntour NVX32-5TA-DS-700C-50, travel 50 mm, fork length 476 mm
HEADSET	ONE PT-1866A-078-1, 1-1/8"-1.5", ID52, Integrated

DRIVETRAIN

SHIFTERS RIGHT	Enviolo Trekking 380 stepless
CRANKSET	Alloy, ISIS, 170 mm
CHAINRING	Gates CARBON DRIVE CDX, 46T
CASSETTE	GATES 22T, CDX
BELT	Gates CARBON DRIVE CDX

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
BRAKE REAR	SHIMANO MT200, hydraulic disc brake

WHEELS

HUB FRONT	ONE, KTMD7F, 36H, QR Type, 6-Bolts
HUB REAR	Enviolo Trekking, 36H, 6-Bolts
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass
RIMS	STARS J25D, Disc, Alloy, 36H
TIRES	Scalato Mondano, 55-622, with puncture protection

COCKPIT

STEM	ONE, Alloy, 31,8mm, ext. 90, adjustable
HANDLEBAR	Alloy, 31.8 x 660 mm
GRIPS LEFT	HERRMANS Altro, ergonomic
GRIPS RIGHT	HERRMANS Altro, ergonomic

PARTS

SADDLE	Selle Royal Explora
SEATPOST	ONE, Alloy, Suspension, 30.9mm

CITY/ SUV SET

FRONT LIGHT	Spanninga NEOS 65, including day running light
REAR LIGHT	Spanninga Pling XE
FENDER	Alloy, extrusion
CARRIER	alloy with MIK HD
FRAME LOCK	AXA Atlas including battery lock

GEOMETRY

FRAME SIZE	460mm (S)	500mm (M)	540mm (L)	580mm (XL)
BB DROP (MM)	75	75	75	75
SEAT TUBE LENGTH (MM)	460	500	540	580
EFFECTIVE TOP TUBE LENGTH (MM)	594	604	619	629
STACK HEIGHT (MM)	663	663	663	663
REACH (MM)	379	379	404	404
SEAT TUBE ANGLE	72°	71°	72°	71°
HEAD TUBE ANGLE	70°	70°	70°	70°
REAR CENTER (MM)	490	490	490	490
HEAD TUBE LENGTH (MM)	175	175	175	175
WHEELBASE (MM)	1125	1125	1150	1150
STEM (MM)	90	90	90	90
CRANKSET (MM)	170	170	170	170
SEATPOST (MM)		350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

eFARAD 6.2

Matte Light Blue

CHF 2'999.–



FRAME SIZE	EAN	Quantity
460mm (S)		
500mm (M)		
540mm (L)		
580mm (XL)		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 540Wh, Smart System
MAX. TORQUE	75Nm / 340%
SUPPORT UP TO SPEED	25km/h
WEIGHT	31.00 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain groundt contact (City and Urban bikes)
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line, 75Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 540Wh
DISPLAY	BOSCH PURION 200

FRAMESET

FRAME	Alloy, easy entry, integrated battery
SUSPENSION FORK	Suntour NVX32-5TA-LO-DS-700C-50, with lock-out, travel 50 mm, fork length 476 mm
HEADSET	ONE PT-1866A-078-1, 1-1/8"-1.5", ID52, Integrated

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	Alloy, ISIS, 170 mm
CHAINRING	42T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-41T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB REAR	SHIMANO FH-QC400, 36H, CL, QR Type
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass
RIMS	STARS J25D, Disc, Alloy, 36H
TIRES	Scalato Mondano, 55-622, with puncture protection

COCKPIT

STEM	ONE, Alloy, 31,8mm, ext. 90, adjustable
HANDLEBAR	Alloy, 31.8 x 660 mm
GRIPS LEFT	HERRMANS Altro, ergonomic
GRIPS RIGHT	HERRMANS Altro, ergonomic

PARTS

SADDLE	Selle Royal Explora
SEATPOST	ONE, Alloy, Suspension, 30.9mm

CITY/ SUV SET

FRONT LIGHT	Spanninga NEOS 40
REAR LIGHT	Spanninga Pling XE
FENDER	Alloy, extrusion
CARRIER	alloy with MIK HD
FRAME LOCK	AXA Atlas including battery lock

GEOMETRY

FRAME SIZE	460mm (S)	500mm (M)	540mm (L)	580mm (XL)
BB DROP (MM)	75	75	75	75
SEAT TUBE LENGTH (MM)	460	500	540	580
EFFECTIVE TOP TUBE LENGTH (MM)	594	604	619	629
STACK HEIGHT (MM)	663	663	663	663
REACH (MM)	379	379	404	404
SEAT TUBE ANGLE	72°	71°	72°	71°
HEAD TUBE ANGLE	70°	70°	70°	70°
REAR CENTER (MM)	490	490	490	490
HEAD TUBE LENGTH (MM)	175	175	175	175
WHEELBASE (MM)	1125	1125	1150	1150
STEM (MM)	90	90	90	90
CRANKSET (MM)	170	170	170	170
SEATPOST (MM)		350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

eFARAD 6.2 27.5"

Matte Light Blue

CHF 2'999.–



FRAME SIZE	EAN	Quantity
440mm (XS)		

SPECIFICATION

BASE INFO

E-SYSTEM	BOSCH Performance, Battery PowerTube 540Wh, Smart System
MAX. TORQUE	75Nm / 340%
SUPPORT UP TO SPEED	25km/h
WEIGHT	31.00 kg

ISO AND EN NORM

ISO norm	EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)
EN norm	EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain grountd contact (City and Urban bikes)
LOAD CAPACITY	150 Kg

E- BIKE PARTS

MOTOR	BOSCH Performance Line, 75Nm
CHARGER	BOSCH 2A
BATTERY	BOSCH PowerTube, 540Wh
DISPLAY	BOSCH PURION 200

FRAMESET

FRAME	Alloy 27.5", easy entry, integrated battery
SUSPENSION FORK	Suntour NVX32-5TA-LO-DS-27.5"-63, with lock-out, travel 63 mm, fork length 477 mm
HEADSET	ONE PT-1866A-078-1, 1-1/8"-1.5", ID52, Integrated

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	Alloy, ISIS, 170 mm
CHAINRING	42T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-41T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 180mm

WHEELS

HUB REAR	SHIMANO FH-QC400, 36H, CL, QR Type
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass
RIMS	STARS J25D, Disc, Alloy, 36H
TIRES	Scalato Mondano, 55-584, with puncture protection

COCKPIT

STEM	ONE, Alloy, 31,8mm, ext. 90, adjustable
HANDLEBAR	Alloy, 31.8 x 660 mm
GRIPS LEFT	HERRMANS Altro, ergonomic
GRIPS RIGHT	HERRMANS Altro, ergonomic

PARTS

SADDLE	Selle Royal Explora
SEATPOST	ONE, Alloy, Suspension, 30.9mm

CITY/ SUV SET

FRONT LIGHT	Spanninga NEOS 40
REAR LIGHT	Spanninga Pling XE
FENDER	Alloy, extrusion
CARRIER	alloy with MIK HD
FRAME LOCK	AXA Atlas including battery lock

GEOMETRY

FRAME SIZE	440mm (XS)
STEM (MM)	90
CRANKSET (MM)	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country



MTB Fully

XF TEAM / XF RC / XF DC



Das Superior XF bietet volle Kontrolle und Laufruhe. Sein Fullsuspension-Rahmen, die durchdachte Geometrie und erstklassigen Komponenten geben dir Selbstvertrauen selbst in den anspruchsvollsten Passagen. Schnell, spielerisch und renntauglich oder einfach perfekt für puren Trail-Spaß.

Le Superior XF offre un contrôle total et une stabilité optimale. Son cadre tout suspendu, sa géométrie bien pensée et ses composants haut de gamme inspirent confiance, même dans les passages les plus exigeants. Rapide, joueur et taillé pour la compétition, ou simplement parfait pour un maximum de plaisir sur les trails.

XF 9.9 Team

Red Carbon / Matte Carbon

CHF 8'999.–



FRAME SIZE	EAN	Quantity
15.5" (S)	8592842207379	
17.5" (M)	8592842204378	
19" (L)	8592842207386	
21" (XL)	8592842207393	

SPECIFICATION

BASE INFO

WEIGHT	10.90 kg

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110-120 mm, Integrated Cable routing, BB92, 3D alloy one pice link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm, ODL
BOTTOM BRACKET	SHIMANO BB-71-41A, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305R1S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO XTR SW-M9250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XTR RD-M9250, Shadow Plus Design
CRANKSET	SHIMANO XTR FC-M9200, 34T
CASSETTE	SHIMANO XTR CS-M9200, 12-speed, 10-51T
CHAIN	SHIMANO XTR CN-M9100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XTR M9200, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL900, 180mm
BRAKE REAR	SHIMANO XTR M9200, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL900, 160mm

WHEELS

WHEELSET FRONT	DT Swiss XRC 1200 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss XRC 1200 SPLINE®, Carbon, CL, 12x148mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe Rick Evo, TL-Ready, XC Pro, 29x2.4", ADDIX Speed
TIRE REAR	Schwalbe Rick Evo, TL-Ready, XC Pro, 29x2.4", ADDIX Speed

COCKPIT

HANDLEBAR	ONE Carbon Integrated Cockpit ICR
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizi:k Ridon X1, Carbon
SEATPOST LEVER	SRAM AXS POD, Dropper Post Lever
SEATPOST	SRAM Reverb AXS dropper post, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	42	42	42	42
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	645
STACK HEIGHT (MM)	583	593	602	611
REACH (MM)	439	460	478	496
SEAT TUBE ANGLE	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1153	1179	1200	1222
HANDLEBAR (MM)	760/60	760/60	760/80	760/80
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L390/T125	L390/T125	L440/T150	L440/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XF 9.6 TEAM

Red Carbon / Matte Carbon

CHF 5'999.–



FRAME SIZE	EAN	Quantity
15.5" (S)	8592842207409	
17.5" (M)	8592842207416	
19" (L)	8592842207423	
21" (XL)	8592842207430	

SPECIFICATION

BASE INFO

WEIGHT	11,4 kg

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110-120 mm, Integrated Cable routing, BB92, 3D alloy one pice link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel
REAR SHOCK	DT Swiss R232 ONE, size 190x45mm, ODL
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-644S, ICR, IPS, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO XT SW-M8250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8250, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8200, 34T
CASSETTE	SHIMANO XT CS-M8200, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO XT M8200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 160mm

WHEELS

WHEELSET FRONT	DT Swiss **XRC** 1700 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss **XRC** 1700 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	42	42	42	42
SEAT TUBE LENGTH (MM)	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	645
STACK HEIGHT (MM)	583	593	602	611
REACH (MM)	439	460	478	496
SEAT TUBE ANGLE	76,3°	76,3°	76,3°	76,3°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1153	1179	1200	1222
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XF 6.6 DC

Matte Green Grey

CHF 2'999.–



FRAME SIZE	EAN	Quantity
15.5" (S)	8592842208925	
17.5" (M)	8592842208932	
19" (L)	8592842208949	
21" (XL)	8592842208956	

SPECIFICATION

BASE INFO

WEIGHT	13.95 kg

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-02-02, Alu X6 Ultimate MTB Trail SU-02.2, Advanced Geometry Travel 130 mm, Integrated Cable Routing, BB92, 3D alloy one pice link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable routing, Dropped seat post ready.
SUSPENSION FORK	RockShox PIKE Select Charger RC, Tapered, DebonAir+, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8100, Shadow Plus Design
CRANKSET	SHIMANO XT FC-M8200, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT64, 180mm
BRAKE REAR	SHIMANO XT M8220, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT64, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS R27-1M, Tubeless, 32H
TIRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS R27-1M, Tubeless, 32H
TIRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	35	35	35	35
SEAT TUBE LENGTH (MM)	368	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	583	609	629	649
STACK HEIGHT (MM)	590	600	609	618
REACH (MM)	428	451	469	487
SEAT TUBE ANGLE	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE	65,6°	65,6°	65,6°	65,6°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1160	1187	1209	1230
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XF 6.2 DC

Gloss Olive

CHF 2'399.–



FRAME SIZE	EAN	Quantity
15.5" (S)	8592842220675	
17.5" (M)	8592842220682	
19" (L)	8592842220699	
21" (XL)	8592842220705	

SPECIFICATION

BASE INFO

WEIGHT	15.40 kg

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	SU-02-02, Alu X6 Ultimate MTB Trail SU-02.2, Advanced Geometry Travel 130 mm, Integrated Cable Routing, BB92, 3D alloy one pice link, Alloy swingarm, SR dropout, Boost 12x148 mm, Inner cable outing, Dropped seat post ready.
SUSPENSION FORK	RockShox PSYLO Silver RC, Tapered, SoloAir, 15x110mm axle, 140mm travel
REAR SHOCK	RockShox Deluxe Select+ RT, size 190x45mm
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-1305, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	SB01, TA12x175.5, M12xP1.0x14.5mm, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6100, Shadow Plus Design
CRANKSET	SHIMANO FC-MT510, 34T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT30, 180mm
BRAKE REAR	SHIMANO MT420, 4 piston, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT30, 180mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm,THRU Type AXLE
RIM FRONT	WTB, KOM LIGHT TEAM i30, Disc, 32H,Tubeless Ready
TIRE FRONT	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	WTB, KOM LIGHT TEAM i30, Disc, 32H,Tubeless Ready
TIRE REAR	Schwalbe Wicked Will Performance, 29x2.40", ADDIX
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE ICR, Alloy, 35mm, 0°
HANDLEBAR	ONE Alloy, 12mm rise, 35mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEATPOST LEVER	SHIMANO SL-MT500-L, Seat post lever
SEATPOST	ONE Sport Dropper Post, Alloy, 30.9mm
SEATPOST CLAMP	ONE CC-080A, 34.9mm, Black

GEOMETRY

FRAME SIZE	15.5" (S)	17.5" (M)	19" (L)	21" (XL)
BB DROP (MM)	35	35	35	35
SEAT TUBE LENGTH (MM)	368	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	583	609	629	649
STACK HEIGHT (MM)	590	600	609	618
REACH (MM)	428	451	469	487
SEAT TUBE ANGLE	75,3°	75,3°	75,3°	75,3°
HEAD TUBE ANGLE	65,6°	65,6°	65,6°	65,6°
REAR CENTER (MM)	430	430	430	430
HEAD TUBE LENGTH (MM)	90	100	110	120
WHEELBASE (MM)	1160	1187	1209	1230
STEM (MM)	35	50	50	50
HANDLEBAR (MM)	760	760	760	760
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	L408/T125	L408/T125	L458/T150	L458/T150

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country





MTB hardtail

XP

Die XP- und XC-Hardtails von Superior bieten eine hervorragende Kombination aus Leichtigkeit, Komfort und sicherem Fahrverhalten. Egal, ob du dich für ein Rennen aufstellst oder zu einer Wochenendtour aufbrichst – diese Bikes sorgen für Effizienz, Fahrspaß und ein perfektes Fahrerlebnis.

Les hardtails XP et XC de Superior offrent un excellent équilibre entre légèreté, confort et stabilité. Que ce soit pour une course ou une sortie le week-end, ces vélos garantissent efficacité, plaisir et une expérience de conduite optimale.

XP 9.6

Matte Dark Chrome / Carbon

CHF 3'199.–



FRAME SIZE	EAN	Quantity
XS	8592842213554	
S	8592842213561	
M	8592842213578	
L	8592842213585	
XL	8592842213592	

SPECIFICATION

BASE INFO

WEIGHT	11.15 kg

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	BF-FB-06, Carbon MTB Race Pro Mid Modulus,Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	DT Swiss F232 ONE, Tapered, 15x110mm axle, 110mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-327S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings
REAR AXLE	SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SW-M6250-IR, Di2, 12-speed
REAR DERAILLEUR	SHIMANO XT RD-M8250, Shadow Plus Design
CRANKSET	SHIMANO SLX FC-M7100, Hollowtech II, 32T
CASSETTE	SHIMANO DEORE CS-M6100, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO M6100, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO M6100, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

WHEELSET FRONT	DT Swiss X 1900 SPLINE®, CL, 15x110mm, Tubeless Ready
WHEELSET REAR	DT Swiss X 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 29x2.35", ADDIX
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.35", ADDIX

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Race, Alloy, 5mm rise, 31.8mm
GRIPS LEFT	ONE Race, Lock-On
GRIPS RIGHT	ONE Race, Lock-On

PARTS

SADDLE	Fizi:k Ridon X5, Alloy
SEATPOST	ONE Race, Carbon, 27.2mm
SEATPOST CLAMP	ONE CC-080A, 31.8mm, Black

GEOMETRY

FRAME SIZE	XS	S	M	L	XL
BB DROP (MM)	57	57	57	57	57
SEAT TUBE LENGTH (MM)	342	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	565	590	615	635	645
STACK HEIGHT (MM)	599	599	603	613	622
REACH (MM)	415	435	455	475	495
SEAT TUBE ANGLE	75,9°	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430	430
HEAD TUBE LENGTH (MM)	90	90	95	105	115
WHEELBASE (MM)	1127	1147	1169	1193	1217
STEM (MM)	60	60	60	80	80
HANDLEBAR (MM)	760	760	760	760	760
CRANKSET (MM)	165	170	170	175	175
SEATPOST (MM)	350	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XP 9.1

Gloss / Matte Red Carbon

CHF 1'899.–



FRAME SIZE	EAN	Quantity
XS		
S		
M	8592842224468	
L		
XL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	BF-FB-06, Carbon MTB Race Pro Mid Modulus,Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-327, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	ZY-THA19A, TA12x175.5, M12xP1.0x14.5L, Black

DRIVETRAIN

REAR DERAILLEUR	SHIMANO DEORE RD-M6200, Shadow Plus Design
CRANKSET	SHIMANO FC-MT520, 32T
CASSETTE	SHIMANO DEORE CS-M6200, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS R27-1M, Tubeless, 32H
TIRE FRONT	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS R27-1M, Tubeless, 32H
TIRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC05P, 31.8mm, Black

GEOMETRY

FRAME SIZE	XS	S	M	L	XL
BB DROP (MM)	57	57	57	57	57
SEAT TUBE LENGTH (MM)	342	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	565	590	615	635	645
STACK HEIGHT (MM)	599	599	603	613	622
REACH (MM)	415	435	455	475	495
SEAT TUBE ANGLE	75,9°	75,5°	75,2°	75,4°	76,4°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	430	430	430	430	430
HEAD TUBE LENGTH (MM)	90	90	95	105	115
WHEELBASE (MM)	1127	1147	1169	1193	1217
STEM (MM)	60	60	60	80	80
HANDLEBAR (MM)	760	760	760	760	760
CRANKSET (MM)	165	170	170	175	175
SEATPOST (MM)	350	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XP 6.6

Brushed Teal / Teal

CHF 1'599.–



FRAME SIZE	EAN	Quantity
XS		
S		
M		
L		
XL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Integrated Cable Routing, BB92, UDH dropout, Boost Thru axle 148x12mm
SUSPENSION FORK	RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-327, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

REAR DERAILLEUR	SHIMANO XT RD-M8200, Shadow ES Design
CRANKSET	SHIMANO XT FC-M8200, 32T
CASSETTE	SHIMANO DEORE CS-M6200, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT54, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT54, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS R27-1M, Tubeless, 32H
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 29x2.35", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS R27-1M, Tubeless, 32H
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.35", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1332, 31.8mm, Black

GEOMETRY

FRAME SIZE	XS	S	M	L	XL
BB DROP (MM)	60	60	60	60	60
SEAT TUBE LENGTH (MM)	303	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	565	590	615	635	642
STACK HEIGHT (MM)	611	611	620	629	639
REACH (MM)	415	435	455	475	495
SEAT TUBE ANGLE	76,2°	75,8°	75°	75,7°	77°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	432	432	432	432	432
HEAD TUBE LENGTH (MM)	90	90	100	110	120
WHEELBASE (MM)	1130	1150	1174	1198	1222
STEM (MM)	60	60	60	80	80
HANDLEBAR (MM)	760	760	760	760	760
CRANKSET (MM)	165	170	170	175	175
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XP 6.2

Gloss Brush Alu / Black

CHF 1'299.–



FRAME SIZE	EAN	Quantity
XS		
S		
M		
L		
XL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Integrated Cable Routing, BB92, UDH dropout, Boost Thru axle 148x12mm
SUSPENSION FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 120mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-327, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

REAR DERAILLEUR	SHIMANO DEORE RD-M7200, Shadow ES Design
CRANKSET	SHIMANO FC-MT520, 32T
CASSETTE	SHIMANO DEORE CS-M6200, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL300, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL300, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS R27-1M, Tubeless, 32H
TIRE FRONT	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS R27-1M, Tubeless, 32H
TIRE REAR	Schwalbe Racing Ralph Performance, 29x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Alloy

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1332, 31.8mm, Black

GEOMETRY

FRAME SIZE	XS	S	M	L	XL
BB DROP (MM)	60	60	60	60	60
SEAT TUBE LENGTH (MM)	303	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	565	590	615	635	642
STACK HEIGHT (MM)	611	611	620	629	639
REACH (MM)	415	435	455	475	495
SEAT TUBE ANGLE	76,2°	75,8°	75°	75,7°	77°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	432	432	432	432	432
HEAD TUBE LENGTH (MM)	90	90	100	110	120
WHEELBASE (MM)	1130	1150	1174	1198	1222
STEM (MM)	60	60	60	80	80
HANDLEBAR (MM)	760	760	760	760	760
CRANKSET (MM)	165	170	170	175	175
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XP 6.1

Gloss Black / Matte Black

CHF 1'099.–



FRAME SIZE	EAN	Quantity
XS		
S		
M		
L		
XL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Integrated Cable Routing, BB92, UDH dropout, Boost Thru axle 148x12mm
SUSPENSION FORK	SR Suntour XCM32, Tapered, Air, LOR, 15x110mm axle, 120mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-327, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

REAR DERAILLEUR	SHIMANO DEORE RD-M6200, Shadow Plus Design
CRANKSET	ONE Race, Alloy
CASSETTE	SHIMANO DEORE CS-M6200, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL300, 180mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL300, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS R27-1M, Tubeless, 32H
TIRE FRONT	Schwalbe Rapid Rob, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE
RIM REAR	STARS R27-1M, Tubeless, 32H
TIRE REAR	Schwalbe Rapid Rob, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Race, Alloy, 31,8mm, -7°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal SRX, 148mm
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1332, 31.8mm, Black

GEOMETRY

FRAME SIZE	XS	S	M	L	XL
BB DROP (MM)	60	60	60	60	60
SEAT TUBE LENGTH (MM)	303	393	431	482	533
EFFECTIVE TOP TUBE LENGTH (MM)	565	590	615	635	642
STACK HEIGHT (MM)	611	611	620	629	639
REACH (MM)	415	435	455	475	495
SEAT TUBE ANGLE	76,2°	75,8°	75°	75,7°	77°
HEAD TUBE ANGLE	66,5°	66,5°	66,5°	66,5°	66,5°
REAR CENTER (MM)	432	432	432	432	432
HEAD TUBE LENGTH (MM)	90	90	100	110	120
WHEELBASE (MM)	1130	1150	1174	1198	1222
STEM (MM)	60	60	60	80	80
HANDLEBAR (MM)	760	760	760	760	760
CRANKSET (MM)	165mm, 32T	170mm, 34T	170mm, 34T	175mm, 34T	175mm, 34T
SEATPOST (MM)	400	400	400	400	400

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country





MTB hardtail

XC

Die XP- und XC-Hardtails von Superior bieten eine hervorragende Kombination aus Leichtigkeit, Komfort und sicherem Fahrverhalten. Egal, ob du dich für ein Rennen aufstellst oder zu einer Wochenendtour aufbrichst – diese Bikes sorgen für Effizienz, Fahrspaß und ein perfektes Fahrerlebnis.

Les hardtails XP et XC de Superior offrent un excellent équilibre entre légèreté, confort et stabilité. Que ce soit pour une course ou une sortie le week-end, ces vélos garantissent efficacité, plaisir et une expérience de conduite optimale.

XC 6.9

Gloss Black

CHF 999.–



FRAME SIZE	EAN	Quantity
16" (S)	8592842213066	
18" (M)	8592842213073	
20" (L)	8592842213080	
22" (XL)	8592842213097	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	**SR Suntour XCM32, Tapered, Air, LOR, 15x110mm axle, 120mm travel**
BOTTOM BRACKET	SHIMANO, Cartridge Bearing
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U6000, 32T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	SHIMANO SM-RT10, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -3°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	635
STACK HEIGHT (MM)	608	617	617	636
REACH (MM)	423	445	465	471
SEAT TUBE ANGLE	75,5°	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°	67°
REAR CENTER (MM)	420	420	420	420
HEAD TUBE LENGTH (MM)	90	100	100	120
WHEELBASE (MM)	1143	1170	1190	1203
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	720	720	720	720
CRANKSET (MM)	170	175	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XC 6.9 MS

Matte Black / Bordeaux

CHF 999.–



FRAME SIZE	EAN	Quantity
S	8592842221955	
M	8592842221962	
L	8592842221979	

SPECIFICATION

BASE INFO

WEIGHT	14.85 kg

ISO AND EN NORM

LOAD CAPACITY	120 Kg
ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm

FRAMESET

BOTTOM BRACKET	SHIMANO, Cartridge Bearing
SUSPENSION FORK	Suspension Air fork, AHEAD 1-1/8", QR Type, 120mm travel
FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
CRANKSET	SHIMANO CUES FC-U6000, 32T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-50T
CHAIN	KMC eGLIDE, LinkGlide
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design

BRAKING SYSTEM

ROTOR FRONT	Rotor 160mm
BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Rotor 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
NIPPLES	SAPIM, Brass
RIM FRONT	STARS J25D, Disc, 32H
SPOKES	SAPIM Galvanized Black
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line

COCKPIT

HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
STEM	ONE Sport, Alloy, 31.8mm, -3°
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
PEDALS	Bearing Pedals with reflector, PP Body
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	S	M	L
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625
STACK HEIGHT (MM)	608	617	617
REACH (MM)	423	445	465
SEAT TUBE ANGLE	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°
REAR CENTER (MM)	440	440	440
HEAD TUBE LENGTH (MM)	90	100	100
WHEELBASE (MM)	1143	1161	1190
STEM (MM)	60	60	60
HANDLEBAR (MM)	720	720	720
CRANKSET (MM)	170	170	170

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XC 6.5

Gloss Dust

CHF 849.–



FRAME SIZE	EAN	Quantity
16" (S)	8592842214742	
18" (M)	8592842214759	
20" (L)	8592842214766	
22" (XL)	8592842214773	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	Suspension Air fork, AHEAD 1-1/8", QRType, 120mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6000-10R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	SHIMANO CUES FC-U4000, 32T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Alhonga, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE Sport, Alloy, 31.8mm, -3°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-617, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	635
STACK HEIGHT (MM)	608	617	617	636
REACH (MM)	423	445	465	471
SEAT TUBE ANGLE	75,5°	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°	67°
REAR CENTER (MM)	420	420	420	420
HEAD TUBE LENGTH (MM)	90	100	100	120
WHEELBASE (MM)	1143	1170	1190	1203
STEM (MM)	60	60	80	80
HANDLEBAR (MM)	720	720	720	720
CRANKSET (MM)	170	175	175	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XC 6.5 MS

Gloss White / Copper

CHF 849.–



FRAME SIZE	EAN	Quantity
S		
M		
L		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	SR Suntour XCM32, Tapered, Air, LO, 15x110mm axle, 120mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartrige, Tapered

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO DEORE SL-M4100-R, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M5120, Shadow Plus Design
CRANKSET	SHIMANO FC-UT400-1, 32T
CASSETTE	SHIMANO DEORE CS-M4100, 10-speed, 11-46T
CHAIN	KMC X10

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	SHIMANO SM-RT10, 180mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, 20mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	S	M	L
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625
STACK HEIGHT (MM)	608	617	617
REACH (MM)	423	445	465
SEAT TUBE ANGLE	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°
REAR CENTER (MM)	440	440	440
HEAD TUBE LENGTH (MM)	90	100	100
WHEELBASE (MM)	1143	1161	1190
HANDLEBAR (MM)	720	720	720
CRANKSET (MM)	170	170	175
SEATPOST (MM)	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XC 6.1

Gloss Black

CHF 729.–



FRAME SIZE	EAN	Quantity
S		
M		
L		
XL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	SR Suntour XCT 30 DS, AHEAD 1-1/8", Coil, QR Type, 100mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4001-9R, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	SHIMANO FC-UT400-1, 32T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	Rotor 160mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, 20mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Sport Wide
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	S	M	L	XL
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	635
STACK HEIGHT (MM)	608	617	617	636
REACH (MM)	423	445	465	471
SEAT TUBE ANGLE	75,5°	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°	67°
REAR CENTER (MM)	420	420	420	420
HEAD TUBE LENGTH (MM)	90	100	100	120
WHEELBASE (MM)	1143	1170	1190	1203
HANDLEBAR (MM)	720	720	720	720
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XC 6.1 MS

Matte Purple

CHF 729.–



FRAME SIZE	EAN	Quantity
16" (S)	8592842219334	
18" (M)	8592842219419	
20" (L)	8592842219495	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	SR Suntour XCT 30 DS, AHEAD 1-1/8", Coil, QRType, 100mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4000-9R, RAPIDFIREPlus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4000, Shadow Design
CRANKSET	SHIMANO CUES FC-U4000, 32T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-46T
CHAIN	SHIMANO CN-LG500

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Alhonga, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 29x2.25", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Sport Wide
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)
BB DROP (MM)	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625
STACK HEIGHT (MM)	608	617	617
REACH (MM)	423	445	465
SEAT TUBE ANGLE	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°
REAR CENTER (MM)	440	440	440
HEAD TUBE LENGTH (MM)	90	100	100
WHEELBASE (MM)	1143	1161	1190
HANDLEBAR (MM)	720	720	720
CRANKSET (MM)	170	170	175

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

XC 6.0

Matte Dark Chrome

CHF 679.–



FRAME SIZE	EAN	Quantity
16" (S)	8592842219310	
18" (M)	8592842219396	
20" (L)	8592842219471	
22" (XL)	8592842219549	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 MTB bicycles
EN norm	EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout,
SUSPENSION FORK	SR Suntour XCT 30 DS, AHEAD 1-1/8", Coil, QRType, 100mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ESSA RD-U2000, Shadow Design
CRANKSET	ONE Sport, Alloy, 34T
CASSETTE	Shimano HG300, 11-45T
CHAIN	KMC NS8

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT200, hydraulic disc brake
ROTOR FRONT	Alhonga, 160mm
BRAKE REAR	SHIMANO MT200, hydraulic disc brake
ROTOR REAR	Alhonga, 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QRType
RIM FRONT	STARS J25D, Disc, 32H
TIRE FRONT	Rubena Cheetah, 29x2,1"
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, 32H
TIRE REAR	Rubena Cheetah, 29x2,1"
SPOKES	SAPIM Zinc
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +6°
HANDLEBAR	ONE Alloy, 20mm rise, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Sport Wide
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE CC-610, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	16" (S)	18" (M)	20" (L)	22" (XL)
BB DROP (MM)	60	60	60	60
SEAT TUBE LENGTH (MM)	406	457	508	559
EFFECTIVE TOP TUBE LENGTH (MM)	580	605	625	635
STACK HEIGHT (MM)	608	617	617	636
REACH (MM)	423	445	465	471
SEAT TUBE ANGLE	75,5°	75,5°	75,5°	75,5°
HEAD TUBE ANGLE	67°	67°	67°	67°
REAR CENTER (MM)	420	420	420	420
HEAD TUBE LENGTH (MM)	90	100	100	120
WHEELBASE (MM)	1143	1170	1190	1203
HANDLEBAR (MM)	720	720	720	720
CRANKSET (MM)	170	170	175	175
SEATPOST (MM)	350	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country





junior

TEAM / F.L.Y. / RACER

Superior Kids-Bikes sind auf Sicherheit, Kontrolle und Fahrspaß ausgelegt. Mit leichten Rahmen, einer komfortablen Geometrie und zuverlässigen Komponenten helfen sie jungen Rider dabei, Selbstvertrauen aufzubauen und jede Fahrt zu genießen – schon ab den allerersten Tritten.

Les vélos pour enfants Superior sont conçus pour offrir sécurité, contrôle et plaisir. Grâce à leur cadre léger, leur géométrie confortable et leurs composants fiables, ils aident les jeunes cyclistes à prendre confiance et à profiter de chaque sortie, dès les premiers coups de pédale.

TEAM 27.7

Gloss Brushed Alu / Red

CHF 1'199.–



FRAME SIZE	EAN	Quantity
XS		
S		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru axle 148x12mm, Inner cable routing.
SUSPENSION FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-212 R5, ZS44/28.6 - ZS56/40
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

REAR DERAILLEUR	SHIMANO DEORE RD-M7200, Shadow ES Design
CRANKSET	ONE Race, Alloy
CASSETTE	SHIMANO DEORE CS-M6200, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL300, 160mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL300, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 28H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J25DB, Tubeless, 28H
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS, 28H, CL, 12X142mm, THRU Type AXLE
RIM REAR	STARS J25DB, Tubeless, 28H
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +3°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE Race, Carbon, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	XS	S
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	330	393
EFFECTIVE TOP TUBE LENGTH (MM)	545	586
STACK HEIGHT (MM)	562	562
REACH (MM)	384	425
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	68°	68°
REAR CENTER (MM)	420	420
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1058	1099
STEM (MM)	45	45
HANDLEBAR (MM)	620	620
CRANKSET (MM)	152mm, 32T	152mm, 32T
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

TEAM 27.7

Gloss Brushed Alu / Rainbow Black

CHF 1‘199.–



FRAME SIZE	EAN	Quantity
XS	8592842225045	
S		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu X6 Ultralite, Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru axle 148x12mm, Inner cable routing.
SUSPENSION FORK	RockShox Judy Silver TK R, Tapered, SoloAir, 15x110mm axle, 100mm travel
BOTTOM BRACKET	SHIMANO BB-MT500PA, PressFit, shell 41x92mm
HEADSET	ACROS AZX-212 R5, ZS44/28.6 - ZS56/40
REAR AXLE	ZY-THA19A, TA12x171.5, M12xP1.0x14.5L, Black

DRIVETRAIN

REAR DERAILLEUR	SHIMANO DEORE RD-M7200, Shadow ES Design
CRANKSET	ONE Race, Alloy
CASSETTE	SHIMANO DEORE CS-M6200, 12-speed, 10-51T
CHAIN	SHIMANO DEORE CN-M6100

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT410, hydraulic disc brake
ROTOR FRONT	SHIMANO RT-CL300, 160mm
BRAKE REAR	SHIMANO MT410, hydraulic disc brake
ROTOR REAR	SHIMANO RT-CL300, 160mm

WHEELS

HUB FRONT	SHIMANO HB-TC500-15-B, 28H, CL, 15x110mm, THRU Type AXLE
RIM FRONT	STARS J25DB, Tubeless, 28H
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
HUB REAR	SHIMANO FH-TC500-MS, 28H, CL, 12X142mm, THRU Type AXLE
RIM REAR	STARS J25DB, Tubeless, 28H
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +3°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE Race, Carbon, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	XS	S
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	330	393
EFFECTIVE TOP TUBE LENGTH (MM)	545	586
STACK HEIGHT (MM)	562	562
REACH (MM)	384	425
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	68°	68°
REAR CENTER (MM)	420	420
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1058	1099
STEM (MM)	45	45
HANDLEBAR (MM)	620	620
CRANKSET (MM)	152mm, 32T	152mm, 32T
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

TEAM 27.3

Gloss Brushed Alu / Red

CHF 899.–



FRAME SIZE	EAN	Quantity
XS	8592842225380	
S		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
SUSPENSION FORK	SR Suntour XCR32, Lock Out, Air, AHEAD 1-1/8", QR Type, 100mm travel
BOTTOM BRACKET	Thun Ibex, BSA
HEADSET	ONE XR-K482-1, 1-1/8"x1.5", ZS44/ZS55, Tapered

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6050-10R, SHORT REACH, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 152mm, 30T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	Rotor 160mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	ONE Sport, 28H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J25DB, Tubeless, 28H
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
HUB REAR	ONE Sport, 28H, CL, M10x135, QR Type
RIM REAR	STARS J25DB, Tubeless, 28H
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +3°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	XS	S
BB DROP (MM)	45	45
SEAT TUBE LENGTH (MM)	330	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	567	567
REACH (MM)	384	423
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	68°	68°
REAR CENTER (MM)	432	432
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1070	1109
STEM (MM)	45	45
HANDLEBAR (MM)	620	620
CRANKSET (MM)	152	152
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

TEAM 27.3

Gloss Brushed Alu / Rainbow Black

CHF 899.–



FRAME SIZE	EAN	Quantity
XS		
S		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
SUSPENSION FORK	SR Suntour XCR32, Lock Out, Air, AHEAD 1-1/8", QR Type, 100mm travel
BOTTOM BRACKET	Thun Ibex, BSA
HEADSET	ONE XR-K482-1, 1-1/8"x1.5", ZS44/ZS55, Tapered

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U6050-10R, SHORT REACH, RAPIDFIRE Plus, 10-speed
REAR DERAILLEUR	SHIMANO CUES RD-U6000, Shadow Plus Design
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 152mm, 30T
CASSETTE	SHIMANO CUES CS-LG400, 10-speed, 11-48T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	Rotor 160mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	ONE Sport, 28H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J25DB, Tubeless, 28H
TIRE FRONT	Schwalbe Racing Ray Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
HUB REAR	ONE Sport, 28H, CL, M10x135, QR Type
RIM REAR	STARS J25DB, Tubeless, 28H
TIRE REAR	Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 27.5x2.25", ADDIX
SPOKES	SAPIM Laser/Race, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +3°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Mini Vivo
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black

GEOMETRY

FRAME SIZE	XS	S
BB DROP (MM)	45	45
SEAT TUBE LENGTH (MM)	330	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	567	567
REACH (MM)	384	423
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	68°	68°
REAR CENTER (MM)	432	432
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1070	1109
STEM (MM)	45	45
HANDLEBAR (MM)	620	620
CRANKSET (MM)	152	152
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

F.L.Y. 27

Gloss Mint

CHF 699.–



FRAME SIZE	EAN	Quantity
XS		
S		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4050-9R, SHORT REACH, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4010, Shadow Design
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 152mm, 30T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-36T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR FRONT	TEKTRO, TR160-35, 160mm
BRAKE REAR	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR REAR	TEKTRO, TR160-35, 160mm

WHEELS

HUB FRONT	ONE Sport, 28H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J20S, Disc, 28H
TIRE FRONT	Schwalbe Smart Sam Performance, 27.5x2.10", ADDIX
HUB REAR	ONE Sport, 28H, CL, M10x135, QR Type
RIM REAR	STARS J20S, Disc, 28H
TIRE REAR	Schwalbe Smart Sam Performance, 27.5x2.10", ADDIX
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +3°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 27"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	XS	S
BB DROP (MM)	50	50
SEAT TUBE LENGTH (MM)	330	393
EFFECTIVE TOP TUBE LENGTH (MM)	545	586
STACK HEIGHT (MM)	516	516
REACH (MM)	397	438
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	68°	68°
REAR CENTER (MM)	432	432
HEAD TUBE LENGTH (MM)	100	100
WHEELBASE (MM)	1060	1101
STEM (MM)	45	45
HANDLEBAR (MM)	620	620
CRANKSET (MM)	152	152
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RACER 27

Gloss Yellow

CHF 579.–



FRAME SIZE	EAN	Quantity
XS	8592842223980	
S		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCS 27.5", 1-1/8",Coil, 100mm travel
BOTTOM BRACKET	Thun Ibex, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 152mm, 30T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	Rotor 160mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J20S, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 27.5x2.10
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J20S, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 27.5x2.10
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +3°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 27"
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	XS	S
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	343	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	566	566
REACH (MM)	383	424
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	69°	69°
REAR CENTER (MM)	435	435
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1064	1104
STEM (MM)	45	45
HANDLEBAR (MM)	620	620
CRANKSET (MM)	152	152
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RACER 27

Gloss Lilac

CHF 579.–



FRAME SIZE	EAN	Quantity
XS		
S		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	75 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCS 27.5", 1-1/8",Coil, 100mm travel
BOTTOM BRACKET	Thun Ibex, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ALTUS RD-M310-L
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 152mm, 30T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	Rotor 160mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type
RIM FRONT	STARS J20S, Disc, 32H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 27.5x2.10
HUB REAR	SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type
RIM REAR	STARS J20S, Disc, 32H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 27.5x2.10
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, +3°
HANDLEBAR	ONE Alloy, 12mm rise, back sweep 9°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 27"
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	Bearing Pedals with reflector, PP Body

GEOMETRY

FRAME SIZE	XS	S
BB DROP (MM)	40	40
SEAT TUBE LENGTH (MM)	343	393
EFFECTIVE TOP TUBE LENGTH (MM)	547	586
STACK HEIGHT (MM)	566	566
REACH (MM)	383	424
SEAT TUBE ANGLE	74°	74°
HEAD TUBE ANGLE	69°	69°
REAR CENTER (MM)	435	435
HEAD TUBE LENGTH (MM)	90	90
WHEELBASE (MM)	1064	1104
STEM (MM)	45	45
HANDLEBAR (MM)	620	620
CRANKSET (MM)	152	152
SEATPOST (MM)	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

TEAM 24

Gloss Brushed Alu / Red

CHF 749.–



FRAME SIZE	EAN	Quantity
11"	8592842225373	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
SUSPENSION FORK	TSR AX1 24" AIR HLO, Lock Out, AHEAD 1-1/8", QR Type, 60mm travel
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4050-9R, SHORT REACH, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4010, Shadow Design
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-36T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	TEKTRO HD-J3120, Post Mount, Hydraulic disc brake
ROTOR FRONT	TEKTRO, TR160-35, 160mm
BRAKE REAR	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR REAR	TEKTRO, TR140-35, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J25D, Tubeless, 20H
TIRE FRONT	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J25D, Tubeless, 20H
TIRE REAR	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	503
REACH (MM)	356
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	393
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	974
STEM (MM)	30
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

TEAM 24

Gloss Brushed Alu / Rainbow Black

CHF 749.–



FRAME SIZE	EAN	Quantity
11"		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
SUSPENSION FORK	TSR AX1 24" AIR HLO, Lock Out, AHEAD 1-1/8", QR Type, 60mm travel
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CUES SL-U4050-9R, SHORT REACH, RAPIDFIRE Plus, 9-speed
REAR DERAILLEUR	SHIMANO CUES RD-U4010, Shadow Design
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-36T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	TEKTRO HD-J3120, Post Mount, Hydraulic disc brake
ROTOR FRONT	TEKTRO, TR160-35, 160mm
BRAKE REAR	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR REAR	TEKTRO, TR140-35, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J25D, Tubeless, 20H
TIRE FRONT	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J25D, Tubeless, 20H
TIRE REAR	Schwalbe Rocket Ron Performance, 24x2.10", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	503
REACH (MM)	356
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	393
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	974
STEM (MM)	30
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

TEAM 20

Gloss Brushed Alu / Red

CHF 659.–



FRAME SIZE	EAN	Quantity
9"		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CLARIS SL-R2000, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO CLARIS RD-R2000
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-32T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR FRONT	TEKTRO, TR140-35, 140mm
BRAKE REAR	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR REAR	TEKTRO, TR140-35, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J25D, Tubeless, 20H
TIRE FRONT	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J25D, Tubeless, 20H
TIRE REAR	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	332
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	332
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	30
CRANKSET (MM)	110
SEATPOST (MM)	200

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

TEAM 20

Gloss Brushed Alu / Rainbow Black

CHF 659.–



FRAME SIZE	EAN	Quantity
9"	8592842225366	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO CLARIS SL-R2000, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO CLARIS RD-R2000
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-32T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR FRONT	TEKTRO, TR140-35, 140mm
BRAKE REAR	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR REAR	TEKTRO, TR140-35, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J25D, Tubeless, 20H
TIRE FRONT	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J25D, Tubeless, 20H
TIRE REAR	Schwalbe Billy Bonkers Performance, 20x2.00", ADDIX
SPOKES	SAPIM Laser, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	332
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	332
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	30
CRANKSET (MM)	110
SEATPOST (MM)	200

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

F.L.Y. 24

Gloss Purple

CHF 679.–



FRAME SIZE	EAN	Quantity
11"		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ACERA RD-M3020
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR FRONT	TEKTRO, TR140-35, 140mm
BRAKE REAR	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR REAR	TEKTRO, TR140-35, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J20S, Disc, 20H
TIRE FRONT	Schwalbe Billy Bonkers Performance, 24x2.00", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J20S, Disc, 20H
TIRE REAR	Schwalbe Billy Bonkers Performance, 24x2.00", ADDIX
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	470
REACH (MM)	365
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	391
HEAD TUBE LENGTH (MM)	100
WHEELBASE (MM)	968
STEM (MM)	30
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

F.L.Y. 24

Gloss Radioactive Yellow

CHF 679.–



FRAME SIZE	EAN	Quantity
11"		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount
FORK	Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-M315-8R, RAPIDFIRE Plus, 8-speed
REAR DERAILLEUR	SHIMANO ACERA RD-M3020
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR FRONT	TEKTRO, TR140-35, 140mm
BRAKE REAR	TEKTRO HD-J3110, Flat Mount, Hydraulic disc brake
ROTOR REAR	TEKTRO, TR140-35, 140mm

WHEELS

HUB FRONT	ONE Sport, 20H, Disc, M9x100mm, QR Type
RIM FRONT	STARS J20S, Disc, 20H
TIRE FRONT	Schwalbe Billy Bonkers Performance, 24x2.00", ADDIX
HUB REAR	ONE Sport, 20H, CL, M10x135, QR Type
RIM REAR	STARS J20S, Disc, 20H
TIRE REAR	Schwalbe Billy Bonkers Performance, 24x2.00", ADDIX
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	470
REACH (MM)	365
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	391
HEAD TUBE LENGTH (MM)	100
WHEELBASE (MM)	968
STEM (MM)	30
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

F.L.Y. 20 VB

Gloss Mint

CHF 499.–



FRAME SIZE	EAN	Quantity
9"		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, V-Brake mount
FORK	Alloy 6061 T6, Advanced Junior, V-Brake
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	microSHIFT TS39-7R, ThumpTap, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO CS-HG200, 7-speed, 12-32T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 20H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 20H
TIRE FRONT	Schwalbe CX Comp, KevlarGuard, 20x1.75", Reflective tape
HUB REAR	ONE Sport, 20H, M10x130, QR Type
RIM REAR	STARS J19SZ, 20H
TIRE REAR	Schwalbe CX Comp, KevlarGuard, 20x1.75", Reflective tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	332
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	332
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	30
CRANKSET (MM)	110
SEATPOST (MM)	200

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

F.L.Y. 20 VB

Gloss Radioactive Yellow

CHF 499.–



FRAME SIZE	EAN	Quantity
9"	8592842224598	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, V-Brake mount
FORK	Alloy 6061 T6, Advanced Junior, V-Brake
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	microSHIFT TS39-7R, ThumpTap, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO CS-HG200, 7-speed, 12-32T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 20H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 20H
TIRE FRONT	Schwalbe CX Comp, KevlarGuard, 20x1.75", Reflective tape
HUB REAR	ONE Sport, 20H, M10x130, QR Type
RIM REAR	STARS J19SZ, 20H
TIRE REAR	Schwalbe CX Comp, KevlarGuard, 20x1.75", Reflective tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25mm rise, 25.4mm
GRIPS LEFT	ONE Kids, Lock-On
GRIPS RIGHT	ONE Kids, Lock-On

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE Sport, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	332
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	332
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	30
CRANKSET (MM)	110
SEATPOST (MM)	200

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RACER 24

Gloss Yellow

CHF 469.–



FRAME SIZE	EAN	Quantity
11"	8592842223997	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCS JR24, 1-1/8",Soft Spring, 50mm travel
BOTTOM BRACKET	Thun Ibex, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV400-8R, REVOSHIFT, 8-speed
REAR DERAILLEUR	SHIMANO TOURNEY TX RD-TX800
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TIRE FRONT	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
HUB REAR	ONE Sport, 24H, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TIRE REAR	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	469
REACH (MM)	357
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	390
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	974
STEM (MM)	30
HANDLEBAR (MM)	540
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RACER 24

Gloss Lilac

CHF 469.–



FRAME SIZE	EAN	Quantity
11"		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCS JR24, 1-1/8",Soft Spring, 50mm travel
BOTTOM BRACKET	Thun Ibex, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV400-8R, REVOSHIFT, 8-speed
REAR DERAILLEUR	SHIMANO TOURNEY TX RD-TX800
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TIRE FRONT	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
HUB REAR	ONE Sport, 24H, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TIRE REAR	Schwalbe Billy Bonkers, KevlarGuard, 24x2.00
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	469
REACH (MM)	357
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	390
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	974
STEM (MM)	30
HANDLEBAR (MM)	540
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RACER 24 ATB

Gloss Green

CHF 559.–



FRAME SIZE	EAN	Quantity
11"	8592842225403	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCS JR24, 1-1/8",Soft Spring, 50mm travel
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV400-8R, REVOSHIFT, 8-speed
REAR DERAILLEUR	SHIMANO TOURNEY TX RD-TX800
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	SHIMANO NEXUS DH-C3000-3N-NT, 32H, 100x140mm
RIM FRONT	STARS J19SZ, 32H
TIRE FRONT	Schwalbe CX Comp, KevlarGuard, 24x1.75", Reflective tape
HUB REAR	ONE Sport, 32H, M10x130, QR Type
RIM REAR	STARS J19SZ, 32H
TIRE REAR	Schwalbe CX Comp, KevlarGuard, 24x1.75", Reflective tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

CITY/ SUV SET

FRONT LIGHT	AXA Echo 15
REAR LIGHT	Spanninga Solo XDS
FENDER	Plastic, Black
CARRIER	Steel, Black

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	469
REACH (MM)	357
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	390
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	974
STEM (MM)	30
HANDLEBAR (MM)	540
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RACER 24 ATB

Gloss Purple

CHF 559.–



FRAME SIZE	EAN	Quantity
11"	8592842225410	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	60 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCS JR24, 1-1/8",Soft Spring, 50mm travel
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV400-8R, REVOSHIFT, 8-speed
REAR DERAILLEUR	SHIMANO TOURNEY TX RD-TX800
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 127mm, 28T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	SHIMANO NEXUS DH-C3000-3N-NT, 32H, 100x140mm
RIM FRONT	STARS J19SZ, 32H
TIRE FRONT	Schwalbe CX Comp, KevlarGuard, 24x1.75", Reflective tape
HUB REAR	ONE Sport, 32H, M10x130, QR Type
RIM REAR	STARS J19SZ, 32H
TIRE REAR	Schwalbe CX Comp, KevlarGuard, 24x1.75", Reflective tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Alloy, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 24"
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

CITY/ SUV SET

FRONT LIGHT	AXA Echo 15
REAR LIGHT	Spanninga Solo XDS
FENDER	Plastic, Black
CARRIER	Steel, Black

GEOMETRY

FRAME SIZE	11"
BB DROP (MM)	45
SEAT TUBE LENGTH (MM)	280
EFFECTIVE TOP TUBE LENGTH (MM)	500
STACK HEIGHT (MM)	469
REACH (MM)	357
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	68°
REAR CENTER (MM)	390
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	974
STEM (MM)	30
HANDLEBAR (MM)	540
CRANKSET (MM)	127
SEATPOST (MM)	300

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RACER 20

Gloss Yellow

CHF 429.–



FRAME SIZE	EAN	Quantity
9"	8592842224000	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
FORK	Alloy 6061 T6, Advanced Junior, V-Brake
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV200-7R, REVOSHIFT, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO MF-TZ500, 7-speed, 14-28T, Freewheel
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 20X1.90", Active Line
HUB REAR	ONE Sport, 24H, Freewheel, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 20X1.90", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Hi-ten, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	331
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	330
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	30
HANDLEBAR (MM)	500
CRANKSET (MM)	110
SEATPOST (MM)	230

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RACER 20

Gloss Lilac

CHF 429.–



FRAME SIZE	EAN	Quantity
9"	8592842224017	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
FORK	Alloy 6061 T6, Advanced Junior, V-Brake
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV200-7R, REVOSHIFT, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO MF-TZ500, 7-speed, 14-28T, Freewheel
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	ONE Sport, 24H, M9x100mm, QR Type
RIM FRONT	STARS J19SZ, 24H
TIRE FRONT	Schwalbe Smart Sam, KevlarGuard, 20X1.90", Active Line
HUB REAR	ONE Sport, 24H, Freewheel, M10x135, QR Type
RIM REAR	STARS J19SZ, 24H
TIRE REAR	Schwalbe Smart Sam, KevlarGuard, 20X1.90", Active Line
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Hi-ten, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	331
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	330
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	30
HANDLEBAR (MM)	500
CRANKSET (MM)	110
SEATPOST (MM)	230

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RACER 20 ATB

Gloss Green

CHF 519.–



FRAME SIZE	EAN	Quantity
9"	8592842225397	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCS JR20, 1-1/8",Soft Spring, 40mm travel
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV200-7R, REVOSHIFT, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO MF-TZ500, 7-speed, 14-28T, Freewheel
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	SHIMANO NEXUS DH-C3000-3N-NT, 32H, 100x140mm
RIM FRONT	STARS J19SZ, 32H
TIRE FRONT	Schwalbe CX Comp, KevlarGuard, 20x1.75", Reflective tape
HUB REAR	ONE Sport, 32H, Freewheel, M10x135, QR Type
RIM REAR	STARS J19SZ, 32H
TIRE REAR	Schwalbe CX Comp, KevlarGuard, 20x1.75", Reflective tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Hi-ten, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

CITY/ SUV SET

FRONT LIGHT	AXA Echo 15
REAR LIGHT	Spanninga Solo XDS
FENDER	Plastic, Black
CARRIER	Steel, Black

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	331
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	330
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	30
HANDLEBAR (MM)	500
CRANKSET (MM)	110
SEATPOST (MM)	230

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

RACER 20 ATB

Gloss Purple

CHF 519.–



FRAME SIZE	EAN	Quantity
9"	8592842225786	

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 Young Adult
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	45 kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout,
SUSPENSION FORK	SR Suntour XCS JR20, 1-1/8",Soft Spring, 40mm travel
BOTTOM BRACKET	Thun Topaz, BSA
HEADSET	ONE XR-K200-1, 1-1/8"x44/30

DRIVETRAIN

SHIFTERS RIGHT	SHIMANO SL-RV200-7R, REVOSHIFT, 7-speed
REAR DERAILLEUR	SHIMANO TOURNEY RD-TY200
CRANKSET	ONE Sport, Alloy, Narrow/Wide, 110mm, 28T
CASSETTE	SHIMANO MF-TZ500, 7-speed, 14-28T, Freewheel
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	Tektro, V-Brake, Alloy
BRAKE REAR	Tektro, V-Brake, Alloy

WHEELS

HUB FRONT	SHIMANO NEXUS DH-C3000-3N-NT, 32H, 100x140mm
RIM FRONT	STARS J19SZ, 32H
TIRE FRONT	Schwalbe CX Comp, KevlarGuard, 20x1.75", Reflective tape
HUB REAR	ONE Sport, 32H, Freewheel, M10x135, QR Type
RIM REAR	STARS J19SZ, 32H
TIRE REAR	Schwalbe CX Comp, KevlarGuard, 20x1.75", Reflective tape
SPOKES	SAPIM Galvanized Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 25.4mm, 0°
HANDLEBAR	ONE Hi-ten, 25.4mm
GRIPS LEFT	ONE Junior Grip
GRIPS RIGHT	ONE Junior Grip

PARTS

SADDLE	Selle Royal Explora Junior 20"
SEATPOST	ONE, Alloy, 27.2mm
SEATPOST CLAMP	ONE ZY-SC1732, 31.8mm, with Quick Release level, Black
PEDALS	VP Components VPE-229, Junior Platform Pedals

CITY/ SUV SET

FRONT LIGHT	AXA Echo 15
REAR LIGHT	Spanninga Solo XDS
FENDER	Plastic, Black
CARRIER	Steel, Black

GEOMETRY

FRAME SIZE	9"
BB DROP (MM)	35
SEAT TUBE LENGTH (MM)	230
EFFECTIVE TOP TUBE LENGTH (MM)	450
STACK HEIGHT (MM)	413
REACH (MM)	331
SEAT TUBE ANGLE	74°
HEAD TUBE ANGLE	67°
REAR CENTER (MM)	330
HEAD TUBE LENGTH (MM)	90
WHEELBASE (MM)	844
STEM (MM)	30
HANDLEBAR (MM)	500
CRANKSET (MM)	110
SEATPOST (MM)	230

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country



trekking & city

BLOX

Die BLOX-Fahrräder von Superior sind die perfekte Wahl für entspannte Fahrten in und außerhalb der Stadt. Komplett ausgestattet mit Beleuchtung, Schutzblechen und Gepäckträgern sind sie bereit für den täglichen Gebrauch und Wochenendausflüge. Praktische Fahrräder mit klarem Design und Fokus auf Komfort.

Les vélos BLOX de Superior sont le choix idéal pour des trajets détendus en ville et au-delà. Entièrement équipés avec éclairage, garde-boue et porte-bagages, ils sont prêts pour le quotidien comme pour les sorties du week-end. Des vélos pratiques au design épuré, axés sur le confort.

BLOX 6.7 T

Matte Brush Alu

CHF 1'149.–



FRAME SIZE	EAN	Quantity
S		
M	8592842224062	
L		
XL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 City and trekking bicycles\t
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Touring Geometry, Integrated Cable Routing, BB BSA
SUSPENSION FORK	SR Suntour NEX-HLO, 1-1/8", Coil, QR Type, 50mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS LEFT	SHIMANO CUES SL-U6001-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
FRONT DERAILLEUR	SHIMANO CUES FD-U6010-L, Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO CUES RD-U6020, Shadow Design
CRANKSET	SHIMANO CUES FC-U6010, Hollowtech II, 46-32T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	Rotor 160mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	SHIMANO DH-3D37-QR, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	Schwalbe Motion Road Cruiser Plus, PunctureGuard, 47-622, Reflective tape
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	Schwalbe Motion Road Cruiser Plus, PunctureGuard, 47-622, Reflective tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, back sweep 15°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1335, 34.9mm, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
REAR LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
FENDER	Alloy, extrusion
CARRIER	Rear Carrier with AVS

GEOMETRY

FRAME SIZE	S	M	L	XL
BB DROP (MM)	70	70	7070	70
SEAT TUBE LENGTH (MM)	410	460	510	560
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
STACK HEIGHT (MM)	592	610	610	630
REACH (MM)	400	415	435	450
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	70°	70°	70°	70°
REAR CENTER (MM)	460	460	460	460
HEAD TUBE LENGTH (MM)	140	160	160	180
WHEELBASE (MM)	1087	1109	1129	1150
STEM (MM)	70	70	90	90
HANDLEBAR (MM)	660	660	660	660
CRANKSET (MM)	170	170	170	170
SEATPOST (MM)	300	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

BLOX 6.7 T MS

Matte Brush Alu

CHF 1'149.–



FRAME SIZE	EAN	Quantity
S		
M		
L		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 City and trekking bicycles\t
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Touring Geometry, Integrated Cable Routing, BB BSA
SUSPENSION FORK	SR Suntour NEX-HLO, 1-1/8", Coil, QR Type, 50mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS LEFT	SHIMANO CUES SL-U6001-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed
FRONT DERAILLEUR	SHIMANO CUES FD-U6010-L, Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO CUES RD-U6020, Shadow Design
CRANKSET	SHIMANO CUES FC-U6010, Hollowtech II, 46-32T
CASSETTE	SHIMANO CUES CS-LG400, 11-speed, 11-45T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	Rotor 160mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	SHIMANO DH-3D37-QR, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	Schwalbe Motion Road Cruiser Plus, PunctureGuard, 47-622, Reflective tape
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	Schwalbe Motion Road Cruiser Plus, PunctureGuard, 47-622, Reflective tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, back sweep 15°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1335, 34.9mm, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
REAR LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
FENDER	Alloy, extrusion
CARRIER	Rear Carrier with AVS

GEOMETRY

FRAME SIZE	S	M	L
BB DROP (MM)	70	70	70
SEAT TUBE LENGTH (MM)	380	460	500
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	592	610	629
REACH (MM)	400	414	429
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	70°	70°	70°
REAR CENTER (MM)	460	460	460
HEAD TUBE LENGTH (MM)	140	160	180
WHEELBASE (MM)	1087	1109	1130
STEM (MM)	70	70	90
HANDLEBAR (MM)	660	660	660
CRANKSET (MM)	170	170	170
SEATPOST (MM)	300	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

BLOX 6.5 T

Matte Black

CHF 899.–



FRAME SIZE	EAN	Quantity
S		
M		
L		
XL		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 City and trekking bicycles\t
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Touring Geometry, Integrated Cable Routing, BB BSA
SUSPENSION FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS LEFT	SHIMANO CUES SL-U4001-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO CUES SL-U4001-9R, RAPIDFIRE Plus, 9-speed
FRONT DERAILLEUR	SHIMANO CUES FD-U4000, Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO CUES RD-U4020, Shadow Design
CRANKSET	SHIMANO CUES FC-U4010-2, 46-30T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-36T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	Rotor 160mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	SHIMANO DH-3D37-QR, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	Schwalbe Motion Road Cruiser Plus, PunctureGuard, 47-622, Reflective tape
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	Schwalbe Motion Road Cruiser Plus, PunctureGuard, 47-622, Reflective tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, back sweep 15°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1335, 34.9mm, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
REAR LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
FENDER	Alloy, extrusion
CARRIER	Rear Carrier with AVS

GEOMETRY

FRAME SIZE	S	M	L	XL
BB DROP (MM)	70	70	7070	70
SEAT TUBE LENGTH (MM)	410	460	510	560
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610	630
STACK HEIGHT (MM)	592	610	610	630
REACH (MM)	400	415	435	450
SEAT TUBE ANGLE	74°	74°	74°	74°
HEAD TUBE ANGLE	70°	70°	70°	70°
REAR CENTER (MM)	460	460	460	460
HEAD TUBE LENGTH (MM)	140	160	160	180
WHEELBASE (MM)	1087	1109	1129	1150
STEM (MM)	70	70	90	90
HANDLEBAR (MM)	660	660	660	660
CRANKSET (MM)	170	170	170	170
SEATPOST (MM)	300	350	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

BLOX 6.5 T MS

Matte Black

CHF 899.–



FRAME SIZE	EAN	Quantity
S		
M		
L		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 City and trekking bicycles\t
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Touring Geometry, Integrated Cable Routing, BB BSA
SUSPENSION FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS LEFT	SHIMANO CUES SL-U4001-L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO CUES SL-U4001-9R, RAPIDFIRE Plus, 9-speed
FRONT DERAILLEUR	SHIMANO CUES FD-U4000, Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO CUES RD-U4020, Shadow Design
CRANKSET	SHIMANO CUES FC-U4010-2, 46-30T
CASSETTE	SHIMANO CUES CS-LG300, 9-speed, 11-36T
CHAIN	KMC eGLIDE, LinkGlide

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	Rotor 160mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	SHIMANO DH-3D37-QR, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	Schwalbe Motion Road Cruiser Plus, PunctureGuard, 47-622, Reflective tape
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	Schwalbe Motion Road Cruiser Plus, PunctureGuard, 47-622, Reflective tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, back sweep 15°, 31.8mm
GRIPS LEFT	ONE Sport Ergo, Lock-On
GRIPS RIGHT	ONE Sport Ergo, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1335, 34.9mm, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FRONT LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
REAR LIGHT	ONE Integrated, StVZO, with Z-Mark Reflector
FENDER	Alloy, extrusion
CARRIER	Rear Carrier with AVS

GEOMETRY

FRAME SIZE	S	M	L
BB DROP (MM)	70	70	70
SEAT TUBE LENGTH (MM)	380	460	500
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	592	610	629
REACH (MM)	400	414	429
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	70°	70°	70°
REAR CENTER (MM)	460	460	460
HEAD TUBE LENGTH (MM)	140	160	180
WHEELBASE (MM)	1087	1109	1130
STEM (MM)	70	70	90
HANDLEBAR (MM)	660	660	660
CRANKSET (MM)	170	170	170
SEATPOST (MM)	300	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

BLOX 6.2 T MS

Matte Soft Green

CHF 799.–



FRAME SIZE	EAN	Quantity
S		
M	8592842224147	
L		

SPECIFICATION

ISO AND EN NORM

ISO norm	ISO 4210-2 City and trekking bicycles\t
EN norm	EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm
LOAD CAPACITY	120 Kg

FRAMESET

FRAME	Alu 6061 T6 Double Butted, Advanced Touring Geometry, Integrated Cable Routing, BB BSA
SUSPENSION FORK	SR Suntour NEX-DS, 1-1/8", Coil, QR Type, 50mm travel
BOTTOM BRACKET	SHIMANO BB-UN101, 122.5mm, BSA, shell 73mm
HEADSET	FSA NO.80, ICR, Semi-Cartrige, 1-1/8"

DRIVETRAIN

SHIFTERS LEFT	SHIMANO ALTUS SL-M315-2L, RAPIDFIRE Plus, 2-speed
SHIFTERS RIGHT	SHIMANO SL-M315-8R, RAPIDFIRE Plus, 8-speed
FRONT DERAILLEUR	SHIMANO TOURNEY FD-TY606-L, Top Swing, Dual Pull
REAR DERAILLEUR	SHIMANO ACERA RD-M3020
CRANKSET	SHIMANO FC-TY501, 46-30T
CASSETTE	SHIMANO CS-HG31, 8-speed, 11-34T
CHAIN	KMC Z8.3

BRAKING SYSTEM

BRAKE FRONT	SHIMANO MT220, hydraulic disc brake
ROTOR FRONT	Rotor 160mm
BRAKE REAR	SHIMANO MT220, hydraulic disc brake
ROTOR REAR	Rotor 160mm

WHEELS

HUB FRONT	SHIMANO HB-QC300, 36H, CL, M9X100mm, QR Type
RIM FRONT	STARS J25D, Disc, Alloy, 36H
TIRE FRONT	Schwalbe Motion Road Cruiser Plus, PunctureGuard, 47-622, Reflective tape
HUB REAR	SHIMANO FH-QC300-HM, 36H, CL, M10X135mm, QR Type
RIM REAR	STARS J25D, Disc, Alloy, 36H
TIRE REAR	Schwalbe Motion Road Cruiser Plus, PunctureGuard, 47-622, Reflective tape
SPOKES	SAPIM Leader, Stainless Black
NIPPLES	SAPIM, Brass

COCKPIT

STEM	ONE, Alloy, 31,8mm, 35°
HANDLEBAR	ONE Alloy, 30mm rise, back sweep 15°, 31.8mm
GRIPS LEFT	ONE Sport, Lock-On
GRIPS RIGHT	ONE Sport, Lock-On

PARTS

SADDLE	Selle Royal Vivo
SEATPOST	ONE, Alloy, 30.9mm
SEATPOST CLAMP	ONE ZY-SC1335, 34.9mm, Black
PEDALS	VP Components VP-836

CITY/ SUV SET

FENDER	Alloy, extrusion
CARRIER	Rear Carrier with AVS

GEOMETRY

FRAME SIZE	S	M	L
BB DROP (MM)	70	70	70
SEAT TUBE LENGTH (MM)	380	460	500
EFFECTIVE TOP TUBE LENGTH (MM)	570	590	610
STACK HEIGHT (MM)	592	610	629
REACH (MM)	400	414	429
SEAT TUBE ANGLE	74°	74°	74°
HEAD TUBE ANGLE	70°	70°	70°
REAR CENTER (MM)	460	460	460
HEAD TUBE LENGTH (MM)	140	160	180
WHEELBASE (MM)	1087	1109	1130
STEM (MM)	90	90	90
HANDLEBAR (MM)	660	660	660
SEATPOST (MM)	300	350	350

* The specifications, colors, and availability of the products can be subjects to alter without prior notification.
For availability and prices, please contact the retailers in your city/country

superior.



Micromobility as a Key to Success

Smart mobility for modern life.

Mobilität verändert sich. Menschen suchen nach schnelleren, gesünderen und effizienteren Möglichkeiten, sich in Städten und darüber hinaus fortzubewegen. Dabei spielt das Fahrrad eine zentrale Rolle: als praktisches Verkehrsmittel, ökologische Alternative und tägliches Werkzeug für mehr Freiheit. Superior sieht in der Mikromobilität eine der wichtigsten Chancen für die Zukunft. Deshalb entwickeln wir Bikes, die Komfort, einfache Handhabung, moderne Technologie und attraktives Design vereinen. Bikes, die nicht nur im Sport, sondern auch im Alltag überzeugen.

La mobilité évolue. Les gens recherchent des moyens plus rapides, plus sains et plus efficaces de se déplacer en ville et au-delà. Le vélo joue ici un rôle essentiel: moyen de transport pratique, alternative écologique et outil de liberté au quotidien. Superior considère la micromobilité comme l'une des grandes opportunités d'avenir. C'est pourquoi nous développons des vélos qui associent confort, facilité d'utilisation, technologie moderne et design attrayant. Des vélos adaptés non seulement au sport, mais aussi à la vie quotidienne.



Ihr Fachhändler // Votre Marchand

Hergestellt und gedruckt in der Schweiz.
Alle Angaben entsprechen dem Stand bei Drucklegung.

Irrtümer, Fehler und Änderungen vorbehalten.
Alle angegebenen Preise sind unverbindliche Empfehlungen.

Sous réserve de modification de prix et modèle.
Tous les prix indiqués sont des recommandations sans engagement.